

# ACCUCOLOR EFX 961 SANDSTONE BG

829306PM

### SAFETY DATA SHEET

REVISION DATE: 03-04-2015 SUPERSEDES: 10-24-2013

# SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: ACCUCOLOR EFX 961 SANDSTONE BG

PRODUCT DESCRIPTION: Epoxy resin INTENDED USE: Adhesive PRODUCT IDENTIFIER: 829306PM

### **COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

# **SECTION 2: HAZARDS IDENTIFICATION**

# **GHS Hazard Symbols:**





GHS Signal Word: Warning

**GHS Classification:** Skin Sensitisation Category 1; Skin Corrosion/Irritation Category 2; Hazardous to the

aquatic environment - Chronic Category 2; Acute Toxicity - Inhalation Dust / Mist

Category 4

GHS Hazard Phrases: Causes skin irritation.; May cause an allergic skin reaction.; Harmful if inhaled.; Toxic

to aquatic life with long lasting effects.

**GHS Precautions:** 

**Safety Precautions:** Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to

fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Collect spillage.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS#       | PERCENT | Classification   | Note |
|---------------|------------|---------|--|------|
| Epoxy resin   | 25068-38-6 | 50 - 70 | Aquatic Chronic 2; H411<br>Eye Irrit. 2; H319<br>Skin Irrit. 2; H315 |      |



# ACCUCOLOR EFX 961 SANDSTONE BG

829306PM

### SAFETY DATA SHEET

|                                   |            |         | Skin Sens. 1; H317      |               |
|-----------------------------------|------------|---------|-------------------------|---------------|
| Epoxy resin                       | 68609-97-2 | 10 - 30 | Skin Irrit. 2; H315     |               |
|                                   |            |         | Skin Sens. 1; H317      |               |
| Polystyrene                       | 9003-53-6  | 5 - 10  | Acute Tox. 4; H332      |               |
|                                   |            |         | Eye Irrit. 2; H319      |               |
|                                   |            |         | Flam. Liq. 3; H226      |               |
|                                   |            |         | Skin Irrit. 2; H315     |               |
| Crystalline silica                | 14808-60-7 | 1 - 5   | Carc. 1A; H350          | * (see below) |
|                                   |            |         | STOT RE 1; H372         |               |
| Polyethylene glycol, propoxylated | 9003-11-6  | 1 - 5   | Aquatic Chronic 3; H412 |               |
|                                   |            |         | Acute Tox. 2; H330      |               |
| Titanium dioxide                  | 13463-67-7 | 1 - 5   | Carc. 2; H351           | * (see below) |
|                                   |            |         | •                       | ì             |

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

### **SECTION 4: FIRST AID MEASURES**

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

### **SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will burn in a fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

# SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the

quantity of the spill, the area in which the spill occurred.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300



# ACCUCOLOR EFX 961 SANDSTONE

829306PM

## SAFETY DATA SHEET

### **SECTION 7: HANDLING AND STORAGE**

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **EXPOSURE LIMITS:**

| Chemical Name      | Note             | ACGIH EXPOSURE LIMITS                 | OSHA PEL  |
|--------------------|------------------|---------------------------------------|---|
| Crystalline silica | * (see<br>below) | 0.025 mg/m3 TWA (respirable fraction) | ((250)/(%SiO2 + 5) mppcf TWA<br>(respirable)); ((10)/(%SiO2 + 2) mg/m3<br>TWA (respirable)); ((30)/(%SiO2 + 2)<br>mg/m3 TWA (total dust)) |
| Titanium dioxide   | * (see<br>below) | 10 mg/m3 TWA                          | 15 mg/m3 TWA (total dust)   |
| Wax, polyethylene  |                  | 2 mg/m3 TWA (fume)                    | Not established   |

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

### **ENGINEERING CONTROL METHODS:**

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter if product is sprayed. Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE: Liquid COLOR: Beige

ODOR: Aromatic Mild
ODOR THRESHOLD: Not established
pH: Not established
FREEZING/MELTING POINT (deg. C): Not established
BOILING POINT (deg. C): Not established



# ACCUCOLOR EFX 961 SANDSTONE BG

829306PM

### SAFETY DATA SHEET

FLASH POINT: Not applicable EVAPORATION RATE: Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

WEIGHT PER GALLON (lbs.): 8.70 SPECIFIC GRAVITY: 1.080

SOLUBILITY: Not established OCTANOL/WATER COEFFICIENT: Not established AUTOIGNITION TEMPERATURE: Not established DECOMPOSITION TEMPERATURE: Not established VISCOSITY: No data available.

SOLIDS (% by weight): 100.0 VOC, weight percent 0.00

### **SECTION 10: STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

### SECTION 11: TOXICOLOGICAL INFORMATION

**Component Toxicity / Toxicology Data:** 

| COMPONENT NAME                    | LD50/LC50                           |
|-----------------------------------|-------------------------------------|
| Fly ash                           | ORAL LD50 RAT > 2,000 MG/KG         |
| Crystalline silica                | ORAL LD50 RAT 500 MG/KG             |
| Polyethylene glycol, propoxylated | INHALATION LC50-4H RAT 320.00 MG/M3 |
| Titanium dioxide                  | ORAL LD50 RAT > 10,000 MG/KG        |

# This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Skin Lungs

Aspiration hazard: No data available.



# ACCUCOLOR EFX 961 SANDSTONE

829306PM

### SAFETY DATA SHEET

Medical Conditions Aggravated by Exposure: Skin disease including eczema and sensitization, Lung disease

# **SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available. PERSISTENCE: No data available. BIOACCUMULATION: No data available.

## This product has not been tested for ecological effects. Relevant information for components is listed below:

| Component:         | Ecotoxicity values:       |
|--------------------|---------------------------|
| No data available. | Acute Toxicity (Fish):    |
|                    | Acute Toxicity (Daphnia): |
|                    | Acute Toxicity (Algae):   |

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

# **SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT: NOT REGULATED NOT REGULATED IMDG: NOT REGULATED

### **SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS** 

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product contains a component that is not on the Australian

Inventory (AICS).

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313



# ACCUCOLOR EFX 961 SANDSTONE BG

Print Date: 03-18-2015 829306PM

# **SAFETY DATA SHEET**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name

CAS#

W

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B D2A

### STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

| Chemical Name/List      |                           | CAS        | Percent      |  |
|-------------------------|---------------------------|------------|--------------|--|
| Quartz                  | (Carcinogen)              | 14808-60-7 | 1 - 5        |  |
| Titanium dioxide        | (Carcinogen)              | 13463-67-7 | 1 - 5        |  |
| Carbon black            | (Carcinogen)              | 1333-86-4  | 0.001 - 0.01 |  |
| Phenyl glycidyl ether   | (Carcinogen)              | 122-60-1   | < 10 ppm     |  |
| Epichlorohydrin         | (Carcinogen)              | 106-89-8   | < 10 ppm     |  |
| Benzene                 | (Carcinogen)              | 71-43-2    | < 10 ppm     |  |
| Methanol                | (Developmental toxin)     | 67-56-1    | < 10 ppm     |  |
| Benzene                 | (Developmental toxin)     | 71-43-2    | < 10 ppm     |  |
| (Phenoxymethyl) oxirane | (Male reproductive toxin) | 122-60-1   | < 10 ppm     |  |
| Epichlorohydrin         | (Male reproductive toxin) | 106-89-8   | < 10 ppm     |  |
| Benzene                 | (Male reproductive toxin) | 71-43-2    | < 10 ppm     |  |

## Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

### **SECTION 16: OTHER INFORMATION**

SDS VERSION DATE: 03-04-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 1 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment

recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.