

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY  
Product code : 100000015045

**Manufacturer or supplier's details**

Company : H.B. Fuller Construction Products  
Address : 1105 South Frontenac  
Aurora, IL, 60504  
Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Sealant  
Restrictions on use : For industrial use only.

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	viscous liquid
Color	white
Odor	Neutral

**GHS Classification**

Germ cell mutagenicity : Category 1B  
Carcinogenicity : Category 1B

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

**Hazard Statements:**

H340 May cause genetic defects. H350 May cause cancer.

**Precautionary Statements:****Prevention:** P201 Obtain special instructions before use. P202 Do not handle until all safety

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

precautions have been read and understood. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:** P405 Store locked up.

**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

**Potential Health Effects****Carcinogenicity:****IARC**

Group 1: Carcinogenic to humans During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO<sub>2</sub>)

14808-60-7

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Known to be human carcinogen During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO<sub>2</sub>)

14808-60-7

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration [%]
calcium carbonate	471-34-1	30 - 50
Quartz (SiO <sub>2</sub> )	14808-60-7	20 - 30
stoddard solvent	8052-41-3	0.1 - 1

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

---

develop. Provide medical care provider with this SDS.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Not combustible.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : none
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
- Specific extinguishing methods :
- Further information : This product is an aqueous mixture that will not burn. Dried product film will burn in a fire.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : No special environmental precautions required.  
Prevent product from entering drains.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : No special precautions are needed in handling this material.
- Conditions for safe storage : Keep container closed when not in use.  
Keep in a dry, cool place.
- Materials to avoid : Do not freeze.  
No special restrictions on storage with other products.
- Storage temperature :  $\geq 40^{\circ}\text{F}$
- 

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## SAFETY DATA SHEET

### TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY

Version 1.0

Revision Date 10/31/2022

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m <sup>3</sup>	CAL PEL
		PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	CAL PEL
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m <sup>3</sup>	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	500 ppm 2,900 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 525 mg/m <sup>3</sup>	OSHA P0
		PEL	100 ppm 525 mg/m <sup>3</sup>	CAL PEL

#### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.  
 In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

Material	: Nitrile rubber
Remarks	: For prolonged or repeated contact use protective gloves.
Eye protection	: Safety glasses
Protective measures	: No special protective equipment required.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: viscous liquid
Color	: white
Odor	: Neutral
Odor Threshold	: no data available
pH	: 7.4 - 8.8
Melting point/freezing point	: 32 °F
Boiling point/boiling range	: 212 °F
Flash point	: Not applicable
Evaporation rate	: is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Vapor pressure	: is not determined
Relative vapor density	: is not determined
Density	: 12.0 - 13.8 lb/gal
Solubility(ies)	
Water solubility	: dispersible
Partition coefficient: n-octanol/water	: no data available
Autoignition temperature	: is not determined

**SECTION 10. STABILITY AND REACTIVITY**

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Hazardous decomposition products	: Stable under normal conditions.

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

No data available

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitization**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT-single exposure**

No data available

**STOT-repeated exposure**

No data available

**Aspiration toxicity**

No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Mobility in soil**

No data available

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.  
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION**

**SARA 311/312 Hazards** : Germ cell mutagenicity  
Carcinogenicity

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SAFETY DATA SHEET****TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY**

Version 1.0

Revision Date 10/31/2022

**SARA 313**

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**US State Regulations****California Prop 65**

Please contact Supplier for more information.

**The ingredients of this product are reported in the following inventories:****TSCA**

All substances listed as active on the TSCA inventory

**AIIC**

On the inventory, or in compliance with the inventory

**DSL**

All components of this product are on the Canadian DSL

**IECSC**

On the inventory, or in compliance with the inventory

**Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

**SECTION 16. OTHER INFORMATION**

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com



## SAFETY DATA SHEET


### TEC® ACCUCOLOR® 850-934 CK SANDED SLATE GRAY

Version 1.0

Revision Date 10/31/2022

#### Further information

##### NFPA:



##### HMIS III:

<b>HEALTH</b>	<b>0*</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.