

Your Base For a Colorful Concrete Floor

See Reverse for
More Information ▶

TEC® Level Set® Wear Topping



Imagine the possibilities with Level Set® Wear Topping. This premium, decorative concrete overlayment allows you to finish your project with style. The product is available in three base colors, and gives you the flexibility to add colorant at the time of mixing to support your design requirements. Very smooth, rapid setting and ideal for high traffic areas, Level Set® Wear Topping also accepts stains, sealants and coatings in 24 hours.

**Pour on Level Set® Wear Topping for a decorative concrete finish.
Add your favorite colors to create an extra strong, extra smooth
surface that makes your ideas shine.**



Level Set[®] Wear Topping

TEC[®] Level Set[®] Wear Topping is a premium, high strength, rapid setting wear topping that provides an ultra-smooth, hard, flat cured surface. It comes in three basic colors, can be barrel applied or pumped into place, accepts integral colorant at mixing and accepts stains, sealers and coatings within 24 hours. Uses include malls, retail floors, lobby designs, light manufacturing, warehouses, finished applications subject to constant foot or vehicle traffic, countertops and correction of imperfections in new construction. This calcium aluminate cement-based topping is mold and mildew resistant and can be polished. For details about TEC[®] product or system warranties, contact your sales associate or visit tecspecialty.com.



Barrel or pump in place for interior applications



Ultra-smooth, cured surface with 6000 psi (42.1 MPa)



Accepts stains, sealers and coatings within 24 hours; integral colorant can be added when mixing

Additional Features and Benefits

- Rapid setting for quick return to service
- Accepts foot traffic in 2-3 hours and rubber wheel traffic within 48 hours
- Single lift applications from ¼"-2" (6-50 mm) neat; can be extended to 5" (127 mm) with appropriate aggregate
- Mold and mildew resistant

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Thickness	Approximate Coverage per 50 lbs. (22.68 kg)
¼" (6 mm)	23 sq. ft. (2.14 m ²)
½" (12 mm)	11.5 sq. ft. (1.07 m ²)
1" (25 mm)	5.6 sq. ft. (0.52 m ²)

Suitable Substrates*

- Concrete

*For other suitable substrates, please contact the TEC[®] Technical Support Team at 1-800-832-9023.

Packaging

50 lb. moisture-resistant bags (22.68 kg)

Bright White (054)

White (057)

Gray (058)

Product #7160184813

Product #7160334813

Product #7160844813

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Bright White, White, or Gray
Yield	0.47 ft ³ /bag (0.013 m ³ /bag)
Working Time	25-35 minutes
pH	11
Storage	Store in cool, dry area away from direct sunlight. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.

Visit tecspecialty.com to learn more