

TEC™



*Performance*

Introducing  
AccuColor EFX® Epoxy Special Effects Grout.  
Superior in performance. Unmatched in design.

*Design*

AccuColor EFX® Epoxy Grout redefines traditional epoxies with improved stain resistance, UV color stability and ease of use.

- Easy installation and clean-up
- Superior stain and chemical resistance
- Excellent UV color stability
- 700+ colors
- Special effects enhancers

# Specify for Performance. Select for Design.

AccuColor EFX® Epoxy Special Effects Grout is a 100% solids epoxy that combines superior performance and unmatched design options into one easy-to-use product.

- Dual-purpose mortar and grout is designed for environments where high chemical and stain resistance is required
- Designed for installing green marble, quarry tile, and other natural stone and moisture sensitive agglomerates
- Ideal for walls, floors and countertops; non-sag on wall applications up to a 1/4" grout joint width

## Ease of Use

- Easy Spread-ability – smooth and creamy texture
- Simple Clean-up – special cleaning agents greatly minimize residue build-up. No additives or wait time required.
- Excellent Grab (to grout float) – reduces mess and waste on wall applications

## Performance

- Outstanding Stain Resistance – resists tough stains better than traditional epoxies
- High Chemical Resistance – exceeds ANSI A118.3 standards
- Superior UV Color Stability – reduces yellowing in lighter grouts

## Technical Data

AccuColor EFX® Epoxy Special Effects Grout, TA-440		
In-Use Performance	ANSI Requirement	Typical Results
Bond Strength (Quarry Tile)	1000 psi (6.9 MPa)	> 1300 psi (9.0 MPa)
7-Day Linear Shrinkage <small>Tested in accordance with ANSI A118.3 Specifications for Chemical Resistance, Water Cleanable, Tile Setting, and Grouting Epoxy</small>	< 0.25% shrinkage	0.06% shrinkage
7-Day Compressive Strength (ASTM C579)	3500 psi (24.2 MPa)	> 5000 psi (34.2 MPa)
7-Day Tensile Strength (ASTM C307)	1000 psi (6.9 MPa)	> 1500 psi (10.3 MPa)
Physical State	Paste, once mixed	
Pot Life at 70°F (21°C)	90 minutes	
Initial Set	16 to 20 hours	
Storage	Store in cool, dry location. Do not store in direct sunlight.	
Shelf Life	Maximum of 1 year from date of manufacture in unopened package.	

## Design

- Trusted AccuColor Brand – unsurpassed color accuracy and consistency
- Standard Color\* Palette – Standard White, Sandstone Beige, Almond, Silverado, Light Buff, Light Smoke, DeLorean Gray, Mocha, Light Pewter, Charcoal Gray, Coffee, Raven
- Special Order\*\* Colors
  - 700+ formulated colors
  - Metallic colors in Bronze, Silver and Gold
  - Special Effects
    - Metallic – Bronze, Silver or Gold enhancers may be selected with any AccuColor Grout color or 650+ options from the AccuColor EFX Epoxy Grout color fan deck
    - Glow-in-the-dark – Green illumination lasts up to 3 hours (limited to light grout colors only)

## Warranty

AccuColor EFX is warranted against grout cracking when used as part of a TEC® brand qualifying 1/8" or 1/4" Crack-Isolation System. See full warranty for details.

\*In-stock and available for immediate delivery

\*\*Special orders fulfilled and delivered within 10 business days. Large-volume orders may require up to 15 business days.

## Packaging (3 Gallon Kit) and Grout Color Options

Part A	1 gallon pail (3.78 L), Resin/Pigment sold separately Colors: 12 standard designer colors, 700+ special order colors, special effects glow-in-the-dark and metallic options
Parts B & C	42 fl. oz. (1.24 L) Part B and 25 lb. (11.34 kg) Part C Part C packaged in 5 gallon plastic pail (18.92 L)

## Packaging (1.5 Gallon Kit) and Grout Color Options

Part A	64 fl. oz. jar (1.89 L), Resin/Pigment sold separately Colors: 12 standard designer colors, 3 special order metallic colors (997 bronze, 998 silver and 999 gold)
Parts B & C	21 fl. oz. (.62 L) Part B and 12.5 lb. (5.67 kg) Part C Part C packaged in 2 gallon plastic pail (7.57 L)



H.B. Fuller Construction Products Inc.  
1105 South Frontenac Street  
Aurora, IL 60504-6451  
www.tecspecialty.com

TEC, the TEC logo, AccuColor and AccuColor EFX are trademarks of H.B. Fuller Construction Products Inc

Form# ACEFXSS R0510-1