



CRACK ISOLATION Fast Track System

SAME DAY INSTALL



7am



TEC® 317 Roll-On Crack Isolation Membrane (ROCI)

- Meets ANSI A118.12 Specs
- Fast drying – ready for tile installation in 2-3 hours
- No mesh required
- Isolates cracks up to 1/8"



10am



TEC® 386/387 Fast Set Ultimate Large Tile Mortar

- Fast-curing formula – grout in 3-4 hours
- Provides extended open time
- Non-sag/non-slump characteristics for wall and floor application



2pm



TEC® 550 Power Grout®

- Fast-curing formula – open to traffic in 4 hours and shower use after 24 hours
- Mold and mildew resistant
- Color accurate, stain and efflorescence resistance




TEC® 317 Roll-On Crack Isolation Membrane (ROCI)

A flexible, mold and mildew resistant crack isolation membrane that forms a monolithic film over floors to stop in-plane cracks in the substrate up to 1/8" (3 mm) from transferring through the tile or stone.

- Meets ANSI A118.12 Specifications for Crack Isolation Membranes
- Apply over new (green) concrete as little as 3 days old
- Easy roller, trowel or spray application
- Fast Drying - ready for tile installation in as little as 2 to 3 hours
- Built-in anti-microbial technology resists mold - providing a zone of inhibition when tested in accordance with ASTM D-5590
- No mesh required



No Slipping on Walls



No Slumping on Floors



Superior Contact



TEC® 386/387 Fast Set Ultimate Large Tile Mortar

A high performing, full contact mortar for installing ceramic, porcelain, and natural stone tile.

- Fast curing formula - grout in 3-4 hour
- Thinset or medium-bed application
- Ideal for use with heavy and large format tile
- Non-sag for wall applications and non-slump for floor applications
- Extended open time
- Mixes to a smooth, creamy consistency for superior handling
- Superior transfer - full coverage with minimum effort
- Interior/exterior use
- Exceeds ANSI A118.4 and ANSI A118.11 specifications
- Zero VOC
- Contains recycled materials*


* Gray formula contains 5% pre-consumer recycled material. White formula contains 5% post-consumer recycled material.




Permanent Stain
Resistance




Fast and Easy to Install



Color Consistency



Single Formula for
Walls and Floors



Crack Resistance



Mold and Mildew
Resistant



TEC® 550 Power Grout®

Power Grout® provides the ultimate in grout performance, combining many of the benefits of epoxy and urethane without the hard-to-use drawbacks and costs.

- Highly stain resistant, never needs sealing
- Fast setting; open to traffic in 4 hours
- Color accurate and resistant to efflorescence
- Universal formula for wall and floor applications. For grout joints from 1/16" to 1/2" wide (1.5 mm to 12 mm)
- Crack and shrink resistant
- Mold and mildew resistant
- Exceeds ANSI A118.7 specifications
- Residential to Extra Heavy Commercial Applications
- Interior/exterior use