



WATERPROOFING / CRACK ISOLATION

# Fast Track System

SAME DAY INSTALL



7am



## TEC® 316 HydraFlex™

- Exceeds ANSI A118.10 / A118.12 Specs
- Built-in antimicrobial product protection
- No mesh required (except for waterproofing installations at changes in-plane and substrate joints)
- Isolates cracks up to 1/4"



10am



## TEC® 386/387 Fast Set Ultimate Large Tile Mortar

- Fast-curing formula – grout in 3-4 hours
- Provides extended open time
- Non-sag/non-slump characteristics for wall and floor application



2pm



## TEC® 550 Power Grout®

- Fast-curing formula – open to traffic in 4 hours and shower use after 24 hours
- Mold and mildew resistant
- Color accurate, stain and efflorescence resistance






## TEC® 316 HydraFlex™

Ready-to-use, flexible, mold and mildew resistant waterproofing crack isolation membrane for interior and exterior applications. Forms a smooth, monolithic, watertight surface over walls, floors and ceilings. HydraFlex™ Membrane stops in-plane cracks up to 1/4" (6 mm) wide at the subfloor from telegraphing through to ceramic and stone tile.

- Exceeds ANSI A118.10 Specifications for Waterproofing Membranes
- Exceeds ANSI A118.12 Specifications for Crack Isolation Membranes
- Built-in antimicrobial product protection
- Fast, easy roller application
- Apply even over green concrete
- One ready-to-use component



No Slipping on Walls



No Slumping on Floors



Superior Contact



## TEC® 386/387 Fast Set Ultimate Large Tile Mortar

A high performing, full contact mortar for installing ceramic, porcelain, and natural stone tile.

- Fast curing formula - grout in 3-4 hours
- Thinset or medium-bed application
- Ideal for use with heavy and large format tile
- Non-sag for wall applications and non-slump for floor applications
- Extended open time
- Mixes to a smooth, creamy consistency for superior handling
- Superior transfer - full coverage with minimum effort
- Interior/exterior use
- Exceeds ANSI A118.4 and ANSI A118.11 specifications
- Zero VOC
- Contains recycled materials\*


\* Gray formula contains 5% pre-consumer recycled material. White formula contains 5% post-consumer recycled material.




Permanent Stain  
Resistance




Fast and Easy to Install



Color Consistency



Single Formula for  
Walls and Floors



Crack Resistance



Mold and Mildew  
Resistant



## TEC® 550 Power Grout®

Power Grout® provides the ultimate in grout performance, combining many of the benefits of epoxy and urethane without the hard-to-use drawbacks and costs.

- Highly stain resistant, never needs sealing
- Fast setting; open to traffic in 4 hours
- Color accurate and resistant to efflorescence
- Universal formula for wall and floor applications. For grout joints from 1/16" to 1/2" wide (1.5 mm to 12 mm)
- Crack and shrink resistant
- Mold and mildew resistant
- Exceeds ANSI A118.7 specifications
- Residential to Extra Heavy Commercial Applications
- Interior/exterior use