

For Your Basic Shower Pan Needs

See Reverse for
More Information ▶



TEC® Floor Mud



If the base of your project isn't strong, everything may crumble. TEC® Floor Mud provides a bed for your interior and exterior tile projects. With easy mixing and excellent dry-pack workability, Floor Mud is convenient for large and small jobs that need flattened and leveled bases.

Cover your bases with TEC® Floor Mud. It flattens and levels concrete and wood substrates up to 9".



Ideal for creating shower bases, TEC® Floor Mud is a Portland cement-based mortar designed for thick setting beds under ceramic or quarry tiles--interior or exterior uses. When mixed to a dry consistency, TEC® Floor Mud allows maximum compaction during tamping. It provides excellent workability to flatten and level concrete and wood substrates from ¾" (19 mm) to 9" (27 cm), with a dry-pack consistency. Just add water or TEC® Acrylbond® AMA acrylic mortar additive to mix. For details about TEC® product or system warranties, contact your sales associate or visit tecspecialty.com.



Easy mixing



Dry-pack consistency

Additional Features and Benefits

- Ideal for creating shower bases
- Excellent workability
- Convenient for small or large jobs
- Easy mixing. Just add water or TEC® Acrylbond® AMA acrylic mortar additive

Coverage

Coverage may vary according to substrate conditions and thickness of application. Select the trowel size that will ensure 100% coverage. Figures below are presented only as guidelines.

Application Depth	Approximate Coverage per 50 lbs. (22.68 Kkg)
¾" (9 mm)	11.33 sq. ft. (1.05 m²)
1" (25 mm)	4.25 sq. ft. (0.39 m²)
2" (50 mm)	2.125 sq. ft. (0.20 m²)
3" (76 mm)	1.42 sq. ft. (0.13 m²)

Packaging

50 lb. (22.68 kg) moisture-resistant bags
Gray

Product #7162044813

Suitable Substrates

When properly prepared, suitable substrates include:

- Cured concrete floors
- Over plywood substrates (with a waterproof membrane)
- Adequately designed wood frame floor systems; see Tile Council of North America (TCNA) Handbook.

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Gray
Pot Life [at 68°F (20°C)]	Approximately 60 minutes.
Application temperature range	40°F to 95°F (4°C to 35°C)
Storage	Store in cool, dry location. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.

Visit tecspecialty.com to learn more