

General Packaging Information

Description	
Width	39.25" (99.7 cm)
Length per Roll	69' (21 m)
Square Footage per Roll	225 ft ² (20.9 m ²)
Quantity per Box	1
Quantity per Pallet	24
Weight per Box*	28 lbs. (12.7 kg)

* Values are an approximation

5. INSTALLATION INSTRUCTIONS**Application**

- Clean subfloor so it is free of debris and dirt.
- Apply TEC® Multipurpose Primer to subfloor and let dry. Refer to label for dilution ratio and installation instructions.
- Measure the area and cut membrane length 6" to 8" (15-20 cm) longer than needed to allow for a trimmed fit. If full coverage is needed, skip step 4.
- If only treating individual cracks, cut membrane 3 times the width of the largest tile you will be installing.
- Lay the pre-cut membrane directly on the subfloor with the release liner side down.
- Trim excess material as needed at walls, corners or termination areas.
- Repeat steps until entire floor is covered, butting all seams. Make sure seams do not overlap.
- Pull release liner off membrane while hand-smoothing ridges and air pockets to ensure a good bond with 100% contact with subfloor.
NOTE: Once release liner is pulled from membrane an immediate bond will form. It may be extremely difficult to pull membrane from floor once bonded.
- Roll entire installation with a 75-100 lb. (35-45 kg) roller.
- Tile immediately or cover to protect from debris and potential damage. The use of TEC® brand mortars and grouts is highly recommended. For curing time, refer to manufacturer's product data sheet.

6. AVAILABILITY

TEC® Premium Tile and Stone Installation Products are available nationwide. To locate TEC® products in your area, please contact:

Phone: 800-832-9002
Website: tecspecialty.com

7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. H.B. Fuller Construction Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product. For Limited Warranty details visit tecspecialty.com. To obtain a hard copy of the Limited Warranty call H.B. Fuller Construction Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES**Technical and safety literature**

To acquire technical and safety literature, please visit our website at tecspecialty.com.

10. FILING SYSTEM

Division 9



tecspecialty.com