

# Higher Performance – More Versatility



## TEC® Flexera® Premium Universal Adhesive



Flexera Premium Universal Adhesive is ideal for installing vinyl tile & plank, carpet tile, VCT and resilient sheet flooring. This breakthrough formulation provides aggressive tack and robust adhesion with up to 12 hours of working time and immediate foot traffic after PSA method installations. The high moisture tolerance of 99% RH & 12 lbs MVER is ideal for residential and commercial applications.

**Contact your local sales rep to request a demo. Have a question? Visit [TECQuestions.com](http://TECQuestions.com).**

To learn more, visit [TECSpecialty.com](http://TECSpecialty.com)

See Reverse for More Information





## Flexera® Premium Universal Adhesive

TEC® Flexera® Premium Universal Adhesive is a solvent-free adhesive formulated for the installation of dimensionally stable LVT & vinyl plank without attached backing, PVC and carpet tile, VCT, quartz tile, approved bio-based tile, fiberglass-backed sheet flooring and vinyl backed resilient sheet flooring. This high strength adhesive is designed for installations over porous and non-porous substrates. TEC Flexera Premium Universal Adhesive is CRI Green Label Plus Certified, and is SCAQMD 1168 compliant.



One adhesive, many uses



Moisture resistant – Up to 99% RH and 12 lbs MVER



Can handle immediate foot traffic after PSA method installation

### Features and Benefits

- Premium PSA offering aggressive tack and robust adhesion with very high shear and peel strength
- Long working time – Up to 12 hours
- Ultra-fast strength build – Immediate foot traffic after PSA method installation
- High moisture tolerance – Up to 99% RH & 12 lbs MVER
- Repositionable installation for dry-set
- Can install Semi-Wet Set or PSA method

### Coverage

Determine recommended trowel size based on flooring type. Coverage will vary with the absorption of substrate and trowel size. Figures below are presented only as guidelines.

Substrate/Flooring Type	Recommended Trowel Size	Approximate Coverage*
Porous substrates	$\frac{1}{16}" \times \frac{1}{16}" \times \frac{1}{16}"$ (1.6 x 1.6 x 1.6 mm) Square-notch trowel	125-175 ft <sup>2</sup> /gal. or 14-20 yd <sup>2</sup> /gal. (12-16 m <sup>2</sup> /3.78 L)
Non-Porous substrates	$\frac{1}{16}" \times \frac{1}{32}" \times \frac{1}{32}"$ (1.6 x 0.8 x 0.8 mm) U-notch trowel	175-250 ft <sup>2</sup> /gal. or 19-28 yd <sup>2</sup> /gal. (16-23 m <sup>2</sup> /3.78 L)
Cushion-Backed or Fiber Glossed-Backed Sheet Vinyl / Smooth Backed Vinyl or Carpet Tile	$\frac{3}{8}"$ Nap roller	250-350 ft <sup>2</sup> /gal. or 27-38 yd <sup>2</sup> /gal. (23-32 m <sup>2</sup> /3.78 L)

\*If recommended spread rate is exceeded, a loss of bond may occur.

### Packaging

1 gallon plastic pail (3.78 L)  
4 gallon plastic pail (15.13 L)

Product #15018427  
Product #15016891

### Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Properly Prepared Gypsum
- Terrazzo
- Radiant Heated Subfloors
- Properly Prepared Sheet Vinyl (Single Layer, fully adhered)
- Portland Based Underlayments
- APA Approved Plywood
- Fiber Cement Underlayment
- Properly Prepared VCT (Single Layer)

### Technical Data

#### Physical Properties

Description	
Base Polymer	Acrylic Polymer
Color	Light Straw
Solids	57-61%
VOC Content	<1 gram per liter
Consistency	Paste
Trowelability	Light, Easy
Shelf Life	Two years in unopened container.
Storage	40°-95°F (4°-35°C)
Application Temperature	50°-90°F (10°-32°C)
Traffic Restrictions	Foot traffic after 12 hours and heavy traffic after 24 hours for Semi-Wet Set. Light foot traffic allowed immediately after rolling, heavy traffic after 12 hours for PSA Method.
Open Time	Up to 12 hours of open time depending on porosity and environmental conditions
Freeze/Thaw Stability	5 cycles at 20°F (-6°C)

Conforms with LEED v4 low emitting interiors.  
Compliant with (CDPH) Standard Method v1.2 VOC Emissions.



To learn more, visit [TECSpecialty.com](http://TECSpecialty.com)



H.B. Fuller Construction Products Inc. | 1105 South Frontenac Street Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems