

## SAFETY DATA SHEET

### TEC® EFX 440-950A JET BLACK

Version 1.0

Revision Date 05/03/2022

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TEC® EFX 440-950A JET BLACK  
Product code : 100000021916

##### Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac  
Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

##### Recommended use of the chemical and restrictions on use

Recommended use : Epoxy resin

Restrictions on use : For industrial use only.

#### SECTION 2. HAZARDS IDENTIFICATION


##### Emergency Overview

Appearance	liquid
Color	black
Odor	aromatic

##### GHS Classification

Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitization : Category 1

##### GHS label elements

Hazard pictograms : 

Signal Word : Warning

##### Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

**SAFETY DATA SHEET**
**TEC® EFX 440-950A JET BLACK**

Version 1.0

Revision Date 05/03/2022

**Precautionary Statements:**

**Prevention:** P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

**Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

**Potential Health Effects**
**Carcinogenicity:**
**IARC**

Group 1: Carcinogenic to humans  
 During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO<sub>2</sub>) 14808-60-7

Group 2B: Possibly carcinogenic to humans  
 During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Carbon black 1333-86-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Known to be human carcinogen  
 During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO<sub>2</sub>) 14808-60-7

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration [%]
Epoxy resin	25068-38-6	50 - 70
Epoxy resin	25085-99-8	50 - 70
Ashes (residues)	68131-74-8	10 - 20
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	10 - 20
Polystyrene	9003-53-6	5 - 10
Quartz (SiO <sub>2</sub> )	14808-60-7	5 - 10
Carbon black	1333-86-4	0.1 - 1
Solvent naphtha (petroleum), medium aliph.	64742-88-7	0.1 - 1

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and

**SAFETY DATA SHEET****TEC® EFX 440-950A JET BLACK**

Version 1.0

Revision Date 05/03/2022

will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product may contain crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

**SECTION 4. FIRST AID MEASURES**

- General advice : Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.  
Get medical attention immediately if irritation develops and persists.  
Remove contaminated clothing and shoes.  
Wash contaminated clothing before reuse.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do NOT induce vomiting.  
If victim is fully conscious, give a cupful of water.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific extinguishing methods :
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, : Refer to protective measures listed in sections 7 and 8.

**SAFETY DATA SHEET**
**TEC® EFX 440-950A JET BLACK**

Version 1.0

Revision Date 05/03/2022

protective equipment and emergency procedures

Environmental precautions : Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
Shovel into suitable container for disposal.

**SECTION 7. HANDLING AND STORAGE**

Technical measures : not applicable

Advice on safe handling : No special precautions required.

Conditions for safe storage : Keep in a dry, cool place.

Materials to avoid : No special restrictions on storage with other products.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m <sup>3</sup>	CAL PEL
		TWA	0.1 mg/m <sup>3</sup>	OSHA P0

**SAFETY DATA SHEET**
**TEC® EFX 440-950A JET BLACK**

Version 1.0

Revision Date 05/03/2022

		(respirable dust fraction)		
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	ACGIH
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	3.5 mg/m <sup>3</sup>	OSHA P0
		TWA (Inhalable particulate matter)	3 mg/m <sup>3</sup>	ACGIH
		PEL	3.5 mg/m <sup>3</sup>	CAL PEL
Solvent naphtha (petroleum), medium aliph.	64742-88-7	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 mg/m <sup>3</sup>	ACGIH
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0

**Personal protective equipment**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Hand protection  
Material : Nitrile rubber
- Eye protection : Safety glasses
- Skin and body protection : Remove and wash contaminated clothing before re-use.
- Protective measures : Avoid contact with skin.
- Hygiene measures : Avoid contact with skin, eyes and clothing.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : black
- Odor : aromatic
- Odor Threshold : no data available
- pH : not applicable
- Melting point/freezing point : is not determined
- Boiling point/boiling range : is not determined
- Flash point : not applicable
- Evaporation rate : is not determined
- Flammability (solid, gas) : Not classified as a flammability hazard

**SAFETY DATA SHEET****TEC® EFX 440-950A JET BLACK**

Version 1.0

Revision Date 05/03/2022

---

Upper explosion limit	:	Upper flammability limit is not determined
Lower explosion limit	:	Lower flammability limit is not determined
Vapor pressure	:	is not determined
Density	:	7.9 - 10 lb/gal
Solubility(ies)	:	
Water solubility	:	is not determined
Partition coefficient: n-octanol/water	:	no data available
Autoignition temperature	:	is not determined
Viscosity	:	
Viscosity, kinematic	:	is not determined

---

**SECTION 10. STABILITY AND REACTIVITY**

Chemical stability	:	The product is chemically stable.
Conditions to avoid	:	not applicable
Hazardous decomposition products	:	Stable under normal conditions.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	:	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate : 164.26 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

**Components:****Ashes (residues):**

Acute oral toxicity	:	LD50 Oral Rat: > 2,000 mg/kg
---------------------	---	------------------------------

**Solvent naphtha (petroleum), medium aliph.:**

**SAFETY DATA SHEET****TEC® EFX 440-950A JET BLACK**

Version 1.0

Revision Date 05/03/2022

Acute inhalation toxicity : LC50 Rat: > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitization**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT-single exposure**

No data available

**STOT-repeated exposure**

No data available

**Aspiration toxicity**

No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Solvent naphtha (petroleum), medium aliph. :**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 800 mg/l  
Exposure time: 96 h  
Test Method: static test

**Persistence and degradability**

No data available

**Bioaccumulative potential**

## SAFETY DATA SHEET

### TEC® EFX 440-950A JET BLACK

Version 1.0

Revision Date 05/03/2022

#### Mobility in soil

No data available

#### Other adverse effects

No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

### SECTION 15. REGULATORY INFORMATION

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act



## SAFETY DATA SHEET

### TEC® EFX 440-950A JET BLACK

Version 1.0

Revision Date 05/03/2022

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### US State Regulations

**California Prop 65** Please contact Supplier for more information.

#### The ingredients of this product are reported in the following inventories:

**TSCA** All substances listed as active on the TSCA inventory

**DSL** All components of this product are on the Canadian DSL


**IECSC Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

## SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

#### Further information

##### NFPA:



##### HMIS III:

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.

## SAFETY DATA SHEET

### TEC® EFX 440-950A JET BLACK

Version 1.0

Revision Date 05/03/2022

---