

SAFETY DATA SHEET

TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Product code : 100000019455

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

 Address : 1105 South Frontenac
 Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Cement, Adhesive

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	powder
Color	blue
Odor	odorless

GHS Classification

 Skin irritation : Category 2
 Serious eye damage : Category 1
 Skin sensitization : Category 1
 Carcinogenicity : Category 1A
 Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
 Specific target organ toxicity - repeated exposure : Category 1

GHS label elements

 Hazard pictograms : 

Signal Word : Danger

SAFETY DATA SHEET
TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects
Carcinogenicity:

IARC	Group 1: Carcinogenic to humans quartz (SiO ₂)	14808-60-7
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	Known to be human carcinogen quartz (SiO ₂)	14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Cement, portland, chemicals	65997-15-1	50 - 70
calcium carbonate	471-34-1	30 - 50
calcium sulfate	7778-18-9	5 - 10
quartz (SiO ₂)	14808-60-7	1 - 5
calcium oxide	1305-78-8	1 - 5
magnesium oxide	1309-48-4	1 - 5
kaolin	1332-58-7	1 - 5

SAFETY DATA SHEET**TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT**

Version 1.0

Revision Date 03/31/2022

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
- If inhaled : If inhaled
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Oxygen or artificial respiration if needed.
- In case of skin contact : Wash off with soap and water.
Remove contaminated clothing. If irritation develops, get medical attention.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
If conscious, drink plenty of water.
Never give anything by mouth to an unconscious person.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
No hazardous combustion products are known
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods :
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.
-

SAFETY DATA SHEET

TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.
Should not be released into the environment.
- Methods and materials for containment and cleaning up : Use approved industrial vacuum cleaner for removal.
Do not use compressed air for cleaning purposes.
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid creating dust.
Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.
Take precautionary measures against static discharges.
Provide for appropriate exhaust ventilation and dust collection at machinery.
- Conditions for safe storage : Keep tightly closed in a dry and cool place.
- Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Cement, portland, chemicals	65997-15-1	TWA (Respirable particulate matter)	1 mg/m ³	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1

SAFETY DATA SHEET
TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

		TWA (Dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Total)	10 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
		PEL (Total dust)	10 mg/m ³	CAL PEL
		PEL (respirable dust fraction)	5 mg/m ³	CAL PEL
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m ³	CAL PEL
		PEL (respirable dust fraction)	5 mg/m ³	CAL PEL
calcium sulfate	7778-18-9	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total)	15 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
		PEL (Total dust)	10 mg/m ³	CAL PEL
		PEL (respirable dust fraction)	5 mg/m ³	CAL PEL
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
quartz (SiO ₂)	14808-60-7	TWA	0.025 mg/m ³	ACGIH

SAFETY DATA SHEET
TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

		(Respirable particulate matter)		
		TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m ³	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
calcium oxide	1305-78-8	TWA	2 mg/m ³	ACGIH
		TWA	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	OSHA P0
		PEL	2 mg/m ³	CAL PEL
magnesium oxide	1309-48-4	TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (fume, total particulate)	15 mg/m ³	OSHA Z-1
		TWA (Total particulate)	10 mg/m ³	OSHA P0
		PEL (Fumes)	10 mg/m ³	CAL PEL
		TWA (Fume - total particulate)	10 mg/m ³	OSHA P0
kaolin	1332-58-7	TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1

SAFETY DATA SHEET
TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

		TWA (Total)	10 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Particulates type

Hand protection
Material : butyl-rubber

Eye protection : Safety glasses with side-shields

Skin and body protection : Long sleeved clothing
Remove and wash contaminated clothing before re-use.
Skin should be washed after contact.

Protective measures : Avoid contact with skin.

Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder
 Color : blue
 Odor : odorless
 Odor Threshold : no data available
 : is not determined
 : is not determined
 Evaporation rate : not applicable
 Upper explosion limit : Upper flammability limit
 is not determined
 Lower explosion limit : Lower flammability limit

SAFETY DATA SHEET**TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT**

Version 1.0

Revision Date 03/31/2022

	is not determined
Density	: 9.2 lb/gal
Solubility(ies)	
Water solubility	: is not determined
Partition coefficient: n-octanol/water	: not applicable
Autoignition temperature	: is not determined
Viscosity	
Viscosity, kinematic	: not applicable

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

SAFETY DATA SHEET**TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT**

Version 1.0

Revision Date 03/31/2022

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****calcium sulfate :**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,970 mg/l
Exposure time: 96 h
Test Method: static test

calcium oxide :

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 1,070 mg/l
Exposure time: 96 h
Test Method: static test

Persistence and degradability

No data available

Bioaccumulative potential**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more

SAFETY DATA SHEET**TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT**

Version 1.0

Revision Date 03/31/2022

restrictive requirements.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

SAFETY DATA SHEET

TEC® ACCUCOLOR® 620-953 UNSANDED STARRY NIGHT

Version 1.0

Revision Date 03/31/2022

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory


DSL Inventories Legend TSCA (USA), DSL (Canada), REACH(Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.