



Synthetic Turf Tape Type F

1. PRODUCT NAME

TEC® Synthetic Turf Tape Type F

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800.832.9023 Technical Support
800.952.2368 Fax
tecspecialty.com

3. DESCRIPTION

TEC Synthetic Turf Tape Type F is a high-performance seaming tape specially designed for installation of synthetic turf with TEC turf adhesives. This waterproof fiber-reinforced polyolefin tape combines high tensile strength and superior tear resistance and is ideal for installation of synthetic turf on athletic playing fields.

Key Features and Benefits

- High strength & high basis weight fiber-reinforced polyolefin tape for extreme durability
- Highly resistant to tears and punctures
- Waterproof
- Complies with FIFA standards

Packaging

100-meter (328 feet) length rolls

Product #15036339

Recommended Applications

- Interior and exterior synthetic turf installations
- Commercial and residential
- Sports fields
- Landscaping and leisure applications

Limitations

- Install only in applications recommended by the synthetic turf manufacturer.

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Physical Properties

TEC Synthetic Turf Tape Type F	
Description	
Basis:	Polyolefin tape reinforced with polyolefin fibres
Weight (EN 1849-2):	Ca. 260 g/cm ²
Tensile strength (length EN 12311-2/A):	Ca. 1450 N/5cm
Tensile strength (width EN 12311-2/A):	Ca. 1300 N/5cm
Elongation (length EN 12311-2/A)	Ca. 25%
Elongation (width EN 12311-2/A)	Ca. 20%
Thickness (EN 9073-2)	Ca. 0.65 mm
Width	30 cm (11.81 inches)
Length	100 m (328 feet)
Color	White
Shelf Life	2 years
Storage Conditions	50°F to 90°F (10°C to 32°C)

5. INSTALLATION INSTRUCTIONS

See TEC turf adhesive Product Data Sheet for seaming installation instructions. Always read and follow the turf manufacturer's installation instructions.

6. AVAILABILITY

TEC premium surface preparation, tile, stone, carpet, wood and resilient floor covering installation products are available nationwide. To locate TEC products in your area, please contact:

Phone: 800-832-9002

Website: tecspecialty.com

7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **H.B. Fuller Construction Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit tecspecialty.com. To obtain a hard copy of the Limited Warranty call H.B. Fuller Construction Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical and safety literature

To acquire technical and safety literature, please visit our website at tecspecialty.com.

10. FILING SYSTEM

Division 9



To learn more, visit TECSpecialty.com



H.B. Fuller Construction Products Inc. | 1105 South Frontenac Street Aurora, IL 60504-6451

