

Use of Triple Flex™ Waterproofing Crack Isolation Membrane With Partial Coverage for Pool and Water Feature Installations

DATE

June 2023

RECOMMENDATION

TEC® Triple Flex™ Waterproofing Crack Isolation Membrane can be used as a secondary waterproofing membrane in pool and water feature installations using the partial coverage method i.e. for waterlines, provided; 1) proper surface preparation guidelines are followed and, 2) the product installation instructions listed on the Product Data Sheet are followed, and 3) an experienced professional tile installer performs the work.

Substrate Preparation & Application

Refer to the Triple Flex Waterproofing Crack Isolation Membrane Product Data Sheet for substrate preparation and application instructions. Also refer to the Oceanside Glasstile *Oceanscapes & Aquascapes Installation Guide* for additional instructions.

Warranty

H.B. Fuller Construction Products provides a 5-year product limited warranty for TEC Triple Flex Waterproofing Crack Isolation Membrane. Refer to the product limited warranty document for details which can be found at tecspecialty.com.

Questions?

Call the Technical Support Hotline at 1-800-832-9023.

This Technical Bulletin has been prepared in good faith based on information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions. The owner or owner's representative is responsible for determining acceptability of the product prior to installation.

To learn more, visit TECspecialty.com

