

When Quick Turnarounds Count



TEC® Level Set® 300 Self-Leveling Underlayment



Ideal for quick turnarounds, TEC® Level Set® 300 allows you to quickly smooth substrates without sacrificing performance. This high quality, calcium aluminate-based, self-leveling underlayment provides you with a flat, extremely smooth and durable surface that is **walkable in 2-3 hours**. And, you can install moisture-sensitive floor coverings in as little as 16-24 hours.

Contact your local sales rep to request a demo. Have a question? Visit TECQuestions.com.



To learn more, visit TECSpecialty.com

See Reverse for More Information





Level Set® 300 Self-Leveling Underlayment

Ideal for fast track applications, TEC® Level Set® 300 is a high-performance, calcium aluminate-based, self-leveling underlayment that provides a flat, extremely smooth, and strong, durable surface for finished flooring installation. It is pourable or pumpable for interior applications, offers exceptional workability for an ultra-smooth surface, is walkable in 2-3 hours, can be applied up to 2" (50 mm) neat in single applications and be featheredged to adjoining elevations. For details about TEC® product or system warranties, contact your sales associate or visit tecspecialty.com.



Exceptional workability for an ultra-smooth surface



Pourable or pumpable for interior applications



Install moisture sensitive floor covering in 16-24 hours

Features and Benefits

- Formulated for fast-track applications – walkable in 2-3 hours
- Up to 2" (50 mm) neat and can be featheredged to adjoining elevations
- Applied up to 5" (12 cm) with proper aggregate
- High compressive strength - 5,500 psi (38.0 MPa)
- Accepts non-moisture sensitive tile and stone in 4 hours
- Contributes to LEED® project points
- Zero VOC

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

| Application Depth | Approximate Coverage per 50 lbs. (22.68 kg) |
|-------------------|---|
| 1/8" (3 mm) | 50 sq. ft. (4.65 m²) |
| 1/4" (6 mm) | 25 sq. ft. (2.32 m²) |
| 1/2" (12 mm) | 12.5 sq. ft. (1.16 m²) |
| 1" (25 mm) | 6.25 sq. ft. (0.58 m²) |
| 2" (50 mm) | 3.125 sq. ft. (0.29 m²) |

Packaging

50 lb. plastic bags (22.68 kg)

50 lb. moisture-resistant bags (22.68 kg)

Product #15030023

Product #15036050

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Pavers
- Cement backerboard
- 3/4" hardwood flooring
- Exterior grade plywood (with reinforcement lath)
- Gypsum substrates—minimum tensile bond strength 72 psi (0.5 MPa)
- Ceramic, porcelain or quarry tile
- Cement or epoxy terrazzo
- Metal
- VCT or full glued down, non-cushioned vinyl sheetgoods
- Oriented Strand Board (OSB) (with reinforcement lath)

Technical Data

Physical Properties

| Description | |
|-----------------------|---|
| Physical State | Dry powder |
| Color | Gray |
| Working Time | 25-35 minutes |
| Walkable | 2-3 hours |
| Flooring Installation | Tile: 3-4 hours Moisture sensitive: 16-24 hours |
| Flow (ASTM C1708) | 5"-6" (12.7-15.2 cm) |
| Storage | Store in cool, dry area away from direct sunlight. Do not store open containers. |
| Shelf Life | Maximum 1 year from date of manufacture in properly stored, unopened package. |



Conforms with LEED v4 low emitting interiors.
Compliant with (CDPH) Standard Method v1.2 VOC Emissions.

To learn more, visit [TECspecialty.com](https://tecspecialty.com)



H.B. Fuller Construction Products Inc. | 1105 South Frontenac Street Aurora, IL 60504-6451



@TECInstallationSystems



tecinstitutionsystems



TECInstallationSystems



TEC Installation Systems