



# Wood Endure™ Glue Assist Adhesive

Updated February 2025

## 1. PRODUCT NAME

TEC® Wood Endure™ Glue Assist Adhesive

## 2. MANUFACTURER

TEC Specialty Products LLC  
1105 South Frontenac Street  
Aurora, IL 60504-6451 U.S.A.  
800.552.6225 Office  
800.832.9023 Technical Support  
800.952.2368 Fax  
tecspecialty.com

## 3. DESCRIPTION

TEC Wood Endure Glue Assist is a fast-curing 100% solids modified silane adhesive designed for supplemental bonding of wide plank flooring. It provides excellent green grab and robust elastomeric adhesion to control floor squeaks and excessive flooring movement. Wood Endure Glue Assist has no width or length limitations and is easy to clean off prefinished flooring. Additional applications include wood floor repairs, wood stair nosings, baseboards and installation of wood tackstrips.

### Key Features and Benefits

- Robust adhesion reduces floor squeaks and excessive flooring movement
- Excellent green grab holds flooring in place
- Easy to clean off prefinished wood flooring
- 100% solids & fast curing
- No width or length limitations

### Packaging

20 oz (591 ml) sausage

Product #10016369

### Coverage

Coverage is user-dependent. Typical coverage for a ¼" (6.4 mm) bead is approximately 50-60 lineal ft (15-18 m) per sausage.

### Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete slabs
- Cured leveling compounds
- OSB (underlayment grade)
- Radiant heated subfloors
- Plywood (underlayment grade)
- Ceramic tile
- Terrazzo
- Cement backer board

### Substrate Preparation

The subfloor must be checked according to NWFA guidelines. Ensure that the subfloor is structurally sound, cured, smooth, dry, clean and free from dust, dirt, grease, paint, old adhesive, curing agents, sealers, cutback or any other contaminants that could interfere with a good adhesive bond.

**Concrete Slab:** Must be cured at least 28 days. Do not use in areas subject to hydrostatic pressure or with pre-existing moisture conditions. pH should be between 7-10. The subfloor must be dry to the touch and not visibly damp. Slab must be prepared to receive flooring in compliance with ASTM F710 and NWFA guidelines. Slabs over a year old with high moisture readings indicate a moisture problem related to hydrostatic pressure, broken water pipes, or improper maintenance. These issues are not covered by our warranty.

**Terrazzo:** Surface should be sanded so that all polishes and glaze compounds are stripped. After sanding, thoroughly vacuum and clean the substrate with mineral spirits and allow to dry before installing the wood flooring.

**APA approved Plywood and OSB Type Subfloors:** Panels must be securely fastened. Eliminate movement with screws. Sand all high joints. Fill and patch low areas. Refer to flooring manufacturer for guidelines of moisture content difference between properly acclimated wood flooring and subfloor materials.

**Radiant Heated Subfloors:** Check flooring manufacturer's specifications to determine if the flooring is approved over radiant heated subfloors. Wood Endure is approved for use on hydronic system radiant heated subfloors, provided the system is fully embedded in concrete. Lightweight toppings must be primed first. Turn off the heat 48 hours prior to the installation and leave the heat off until 48 hours after the installation is completed.

### Storage

Store at a moderate room temperature. Protect adhesive from freezing. Refer to the Technical Data section of this PDS, for more information.

### Shelf Life

Maximum of 1 year from date of manufacture in unopened container.

### Limitations

- Interior use only.
- Do not use on wet, dusty or contaminated substrates.
- Subfloor must be dry.
- Do not use in areas subject to hydrostatic pressure.
- Room temperature should be between 65°F (18°C) and 90°F (35°C) during application.
- When installing unfinished wood flooring, wait a minimum of 48 hours before sanding.
- Glue assist installation is for bonding only and does not provide moisture control.
- Glue assist does not change the required nailing schedule.

### Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC brand product(s) under normal environmental and working conditions. Because each project is different, TEC Specialty Products LLC cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

## 4. TECHNICAL DATA

### Physical Properties

TEC Wood Endure Glue Assist Adhesive	
Description	
Tensile Strength	>100 psi
Elongation	125%
Application Room Temperature	Between 65°F (18°C) and 90°F (35°C)
Flash Point	>200°F (>93.3°C)
Color	White
Cure Time	Light foot traffic after 8-10 hours, heavy foot traffic after 24 hours.
Shelf Life	One year from date of manufacture; stored at 50-80°F (10-26°C).

## 5. INSTALLATION INSTRUCTIONS

### Application

Always read and follow the flooring manufacturer's installation instructions and NWFA installation guidelines for glue-assisted nail down.

1. Cut the sausage foil below the end-clip and place the sausage into the dispense gun.
2. Apply a ¼" (6.3 mm) diameter bead in a serpentine pattern with the full curve (peak-to-peak) distance approximately twice the width of the board. The adhesive should cover the entire length and full width of the board. Adhesive may be applied to the subfloor or the back of the flooring.

## Product Data

3. Apply only as much adhesive as can be installed within 15-30 minutes.
4. Press the floor into place and apply a downward force to the board surface when nailing to ensure flooring does not lift away from subfloor.

#### Clean-up

Remove the adhesive from the wood floor surface as soon as possible before the adhesive dries. Use a soft cloth and Mineral Spirits carefully to not harm the finish.

### 6. AVAILABILITY

TEC premium surface preparation, tile, stone, carpet, wood and resilient floor covering installation products are available nationwide. To locate TEC products in your area, please contact:

Phone: 800-832-9002

Website: [tecspecialty.com](http://tecspecialty.com)

### 7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **TEC Specialty Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit [tecspecialty.com](http://tecspecialty.com). To obtain a hard copy of the Limited Warranty call TEC Specialty Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

### 8. MAINTENANCE

Not applicable

### 9. TECHNICAL SERVICES

#### Technical and safety literature

To acquire technical and safety literature, please visit our website at [tecspecialty.com](http://tecspecialty.com).

### 10. FILING SYSTEM

Division 9



To learn more, visit [TECspecialty.com](http://TECspecialty.com)



TEC Specialty Products LLC | 1105 South Frontenac Street, Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems