

LEVEL-HEADED. HEAVY DUTY. RENOVATION READY.



Level Set® 350 Self-Leveling Underlayment

Built for speed and reliability, Level Set® 350 is a high-performance, hybrid self-leveling underlayment designed for fast-track renovations and multi-family housing. It pours from 1/4" to 2" without extension and delivers high compressive strength, high flow, easy placement, and ultra-low shrinkage. Whether you're working over distressed gypsum, concrete, wood, or mixed substrates, it helps you prep quickly and confidently. Pour fast. Finish flat. Work smarter with TEC®.



Visit TECspecialty.com



Level Set® 350 Self-Leveling Underlayment



High flow and easy placement



Up to 40-60 minutes working time



Walkable in 2-4 hours

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Ceramic, porcelain or quarry tile
- Pavers
- Cement or epoxy terrazzo
- Cement backerboard
- Metal
- VCT or full glued down, non-cushioned vinyl sheetgoods
- Exterior grade plywood (with reinforcement lath)
- Oriented Strand Board (OSB) (with reinforcement lath)
- Gypsum substrates (properly primed) with minimum tensile bond strength 72 psi (0.5 MPa)



**High compressive strength
>5,500 psi**
Ultra-durable subfloor



**Install flooring
as soon as 24 hours**

ADDITIONAL FEATURES AND BENEFITS

- Low-Prep – No CSP requirement, can install over properly prepared adhesive
- High flow & easy placement – Reduces labor and installation time
- Compatibility – Use on distressed gypsum, concrete, wood and mixed substrates

Packaging

50 lb. paper bags (22.68 kg)

Product # 10015817

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Depth	Approximate Weight in Pounds per Square Foot (kg/m ²)	Approximate Coverage per 50 lbs. (22.68 kg)
1/4" (6 mm)	2.2-2.6 (10.7-12.7)	25 sq. ft. (2.32 m ²)
1/2" (12 mm)	4.6-5.3 (22.5-25.9)	12.5 sq. ft. (1.16 m ²)
1" (25 mm)	9.1-10.5 (44.4-51.3)	6.25 sq. ft. (0.58 m ²)
1 1/2" (38 mm)	13.7-15.8 (66.9-77.1)	2.778 sq. ft. (0.25 m ²)
2" (50 mm)	18.2-21.0 (88.8-102.6)	3.125 sq. ft. (0.29 m ²)

For details about TEC® product or system warranties, contact your sales associate or visit tecspecialty.com.

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Gray
Working Time	40-60 minutes*
Heal Time (ASTM C1708)	30-40 minutes*
Walkable	2-3 hours*
Flooring Installation	24-48 hours depending on flooring
Speed of Flow (ASTM C1708 ISO 8 capillary flow cup)	15-20 seconds*
Flow (ASTM C1708)	5-6 inches (12.7-15.2 cm)*
Storage	Store in a cool, dry area, away from direct sunlight. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened plastic package. Maximum 9 months for paper package.

*Temperature and humidity will affect flow, working time and set time.



**Scan for
Online
Coverage
Calculator**

Conforms with LEED® v4 low emitting interiors. Compliant with (CDPH) Standard Method v1.2 VOC Emissions.



To learn more, visit tecspecialty.com



TEC Specialty Products LLC.
1105 South Frontenac Street
Aurora, IL 60504-6451



TECInstallationSystems



@tecinstallationsystems



TECInstallationSystems



TEC Installation Systems

©Copyright 2025 TEC Specialty Products LLC.
TEC®, the TEC® logo and Microblast™ are trademarks of
TEC Specialty Products LLC.

SSLS350_N0525-16