

Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Fortane® SL-1C PW Product code : 100000033721

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Cement, Adhesive

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	powder
Color	grey
Odor	odourless

GHS Classification

Skin irritation : Category 2
Serious eye damage : Category 1
Skin sensitisation : Category 1
Carcinogenicity : Category 1A

Specific target organ toxicity -

single exposure

: Category 3 (Respiratory system)

Specific target organ toxicity - : Category 1

repeated exposure

GHS label elements

Hazard pictograms :







Signal Word : Danger

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

quartz (SiO2) 14808-60-7 quartz (SiO2) 14808-60-7

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

quartz (SiO2) 14808-60-7 quartz (SiO2) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
quartz (SiO2)	14808-60-7	50 - 70
cement, portland, chemicals (< 1% quartz)	65997-15-1	20 - 30
calcium carbonate	471-34-1	10 - 20
limestone	1317-65-3	10 - 20
Cement, alumina, chemicals	65997-16-2	5 - 10
calcium sulfate	7778-18-9	5 - 10
magnesium oxide	1309-48-4	1 - 5
quartz (SiO2)	14808-60-7	1 - 5
calcium oxide	1305-78-8	1 - 5
mica (Dust)	12001-26-2	1 - 5
Feldspar-group minerals	68476-25-5	1 - 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES



Fo	rtan	△ (R)	SI	-1C	P	N
	Laii	ヒィン	\mathbf{u}	- 10		

Version 0.0 Revision Date 00/00/0000

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

If inhaled : If inhaled

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Oxygen or artificial respiration if needed.

In case of skin contact : Wash off with soap and water.

Remove contaminated clothing. If irritation develops, get

medical attention.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do not induce vomiting. Seek medical attention if symptoms

develop. Provide medical care provider with this SDS.

If conscious, drink plenty of water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

May cause respiratory irritation.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

No hazardous combustion products are known

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

Further information

methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

: Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Should not be released into the environment.

Methods and materials for containment and cleaning up

Use approved industrial vacuum cleaner for removal.
 Do not use compressed air for cleaning purposes.
 Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid creating dust.

Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Take precautionary measures against static discharges. Provide for appropriate exhaust ventilation and dust collection

at machinery.

Conditions for safe storage : Keep tightly closed in a dry and cool place.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable	0.05 mg/m3	NIOSH REL



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

		dust)		
		TWA	0.1 mg/m3	OSHA P0
		(Respirable		
		fraction)		
		TWA	0.05 mg/m3	OSHA Z-1
		(Respirable	g,	
		dust)		
		PEL	0.05 mg/m3	CAL PEL
		(Respirable	0.00 1119/1110	O/ILI LL
		dust)		
		TWA	0.1 mg/m3	OSHA P0
			0.1 mg/ms	USHA PU
		(respirable		
	05007.45.4	dust fraction)	4	400111
cement, portland, chemicals (<	65997-15-1	TWA	1 mg/m3	ACGIH
1% quartz)		(Respirable		
		particulate		
		matter)		
		TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA	5 mg/m3	OSHA Z-1
		(respirable		
		fraction)		
		TWA (Dust)	50 Million	OSHA Z-3
		(,	particles per cubic	
			foot	
		TWA (Total)	10 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(Respirable	3 -	
		fraction)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)	10 mg/o	
		TWÁ	5 mg/m3	OSHA P0
		(respirable	J. M.	
		dust fraction)		
		PEL (Total	10 mg/m3	CAL PEL
		dust)	10 1119/1110	0/12122
		PEL	5 mg/m3	CAL PEL
		(respirable	Jg	
		dust fraction)		
calcium carbonate	471-34-1	PEL (Total	10 mg/m3	CAL PEL
Calcium carbonate	771 54 1	dust)	10 mg/mo	OALTEL
		PEL	5 mg/m3	CAL PEL
		(respirable	J IIIg/IIIJ	OALFEL
		dust fraction)		
			F	MICCLIDE
		TWA	5 mg/m3	NIOSH REL
		(Respirable)	10	MOCHER
Parada	1047.05.0	TWA (total)	10 mg/m3	NIOSH REL
limestone	1317-65-3	TWA	5 mg/m3	NIOSH REL
		(Respirable) TWA (total)	10 mg/m2	NIOSH REL
			10 mg/m3	
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA Z-1
		IVVA	J Hig/IIIS	OSHA Z-1



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

		(respirable fraction)		
		TWA (Total)	15 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(Respirable		
		fraction)		
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(respirable	3 mg/m3	OOHATO
		dust fraction)		
calcium sulfate	7778-18-9	TWA	5 mg/m3	NIOSH REL
Calciairi Sallate	7770 10 3	(Respirable)	3 mg/m3	MIOOTTKEE
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total)	15 mg/m3	OSHA Z-1
			15 mg/ms	USHA Z-1
		dust) TWA	E ma/m2	OSHA Z-1
			5 mg/m3	USHA Z-1
		(respirable		
		fraction)	45/0	OOLIA DO
		TWA (Total)	15 mg/m3	OSHA PO
		TWA	5 mg/m3	OSHA P0
		(Respirable		
		fraction)	10 / 0	4.0011.1
		TWA	10 mg/m3	ACGIH
		(Inhalable		
		particulate		
		matter)	45 / 0	00114 D0
		TWA (Total	15 mg/m3	OSHA P0
		dust)	- / O	00114 D0
		TWA	5 mg/m3	OSHA P0
		(respirable		
		dust fraction)	10 / 0	OAL DEL
		PEL (Total	10 mg/m3	CAL PEL
		dust)	_ , _	
		PEL	5 mg/m3	CAL PEL
		(respirable		
		dust fraction)	10 / 0	100"
		TWA	10 mg/m3	ACGIH
		(Inhalable		
		particulate		
	4000 10 1	matter)	10 / 0	100"
magnesium oxide	1309-48-4	TWA	10 mg/m3	ACGIH
		(Inhalable		
		particulate		
		matter)	45 / 5	00:11 = :
		TWA (fume,	15 mg/m3	OSHA Z-1
		total		
		particulate)		00111 = 1
		TWA (Total	10 mg/m3	OSHA P0
		particulate)		
		PEL (Fumes)	10 mg/m3	CAL PEL
		TWA (Fume -	10 mg/m3	OSHA P0
		total		



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

		particulate)		
quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
calcium oxide	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
		PEL	2 mg/m3	CAL PEL
mica (Dust)	12001-26-2	TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	3 mg/m3	OSHA P0
		TWA (Respirable)	3 mg/m3	NIOSH REL

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management

measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within

recommended exposure guidelines.

Filter type : Particulates type

Hand protection



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

Material : butyl-rubber

Eye protection : Safety glasses with side-shields

Skin and body protection : Long sleeved clothing

Remove and wash contaminated clothing before re-use.

Skin should be washed after contact.

: Avoid contact with skin. Protective measures

: Avoid contact with skin, eyes and clothing. Hygiene measures

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder Color grey Odor odourless

Odor Threshold no data available

> : is not determined is not determined

Flash point is not determined Evaporation rate : Not applicable

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Density : 11.2 lb/gal

Solubility(ies)

Water solubility : is not determined Partition coefficient: n-: Not applicable

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic Not applicable

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Hazardous decomposition

products

: No decomposition if stored and applied as directed.



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

calcium sulfate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,970 mg/l

Exposure time: 96 Hours Test Method: static test

calcium oxide:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 1,070 mg/l

Exposure time: 96 Hours



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

Test Method: static test

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

Special precautions for user

Not applicable

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



Fortane® SL-1C PW

Version 0.0 Revision Date 00/00/0000

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitisation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

California Prop 65 , which is/are known to the State of California to cause cancer, and

 quartz (SiO2)
 14808-60-7

 acetaldehyde
 75-07-0

 quartz (SiO2)
 14808-60-7

 titanium dioxide
 13463-67-7

, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to

www.P65 Warnings. ca. gov.

lithium carbonate 554-13-2

The ingredients of this product are reported in the following inventories:

TCSI Not in compliance with the inventory

TSCA All substances listed as active on the TSCA inventory

AIIC Not in compliance with the inventory

DSL All components of this product are on the Canadian DSL

ENCS

Not in compliance with the inventory
ISHL

Not in compliance with the inventory
KECI

Not in compliance with the inventory
PICCS

Not in compliance with the inventory
IECSC

Not in compliance with the inventory
Not in compliance with the inventory
Not in compliance with the inventory

CHINV The formulation contains substances listed on the Swiss



	Fortane® SL-1C PW	
Version 0.0	Revision Date 00/00/0000	

Inventory

REACH Not in compliance with the inventory

Not in compliance with the inventory

Not in compliance with the inventory

TECI Not in compliance with the inventory


Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AllC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.