

# **Universal Seam Sealer**

Updated September 2025

#### 1. PRODUCT NAME

TEC® Universal Seam Sealer (131)

#### 2. MANUFACTURER

TEC Specialty Products LLC 1105 South Frontenac Street Aurora, IL 60504-6451 U.S.A. 800.832.9002 Customer Service 800.832.9023 Technical Support tecspecialty.com

# 3. DESCRIPTION

TEC® Universal Seam Sealer is a latex based, non-flammable, carpet seam sealer specially formulated to prevent edge raveling and to seal the seams of most commercial and outdoor carpets including vinyl backs in direct glue down, stretch in, and double glue down installations. It is compatible with most carpet backings. It is fast setting and moisture proof. Not for use with vinyl sheet goods.

# **Key Features and Benefits**

- · Solvent free
- Non-flammable
- · Moisture proof

#### **Packaging**

8 fl. oz. bottle (.473 L)

Product #15036264

#### Coverage

Approximately 160 lineal feet per 8 fl. oz. bottle.

# **Suitable Substrates**

ActionBac

Jute

Latex unitary

Wovens

· Rubber backed

• Urethane (attached cushion)

# **Storage**

Store indoors only. Protect from freezing.

#### Shelf Life

Maximum of 1 year from date of manufacture in unopened container.

# Limitations

- · Not for use with vinyl sheet goods.
- Avoid contact with the nap of the carpet; clean immediately with soap and water. Dried adhesive can be removed with mineral spirits, used sparingly.
- · Protect from freezing

#### **Cautions**

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC® brand product(s) under normal environmental and working conditions. Because each project is different, TEC Specialty Products LLC cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

# 4. TECHNICAL DATA

# **Physical Properties**

TEC® Universal Seam Sealer (131)	
Description	
Base	Latex
Physical State	Thin syrup
Color	White (dries clear)
Open Time	25-30 Minutes
VOC/Liter of Material	34 g/L
Freeze/Thaw Stability	Do not freeze

# 5. INSTALLATION INSTRUCTIONS

# **Application**

When using the hot melt method of seam preparation, proper application of this product should be limited to just the backing edge and base of carpet nap. After the proper amount of TEC® Universal Seam Sealer has been put along either edge of the carpet, it must be rubbed into the edge. Be careful not to transfer adhesive onto the top of the carpet nap. Allow to completely dry prior to constructing a hot melt seam.

When using direct glue down or double bond methods of seam preparation - Apply a 1/8" bead with the applicator tip positioned at the carpets primary backing and the base of the carpet nap. Immediately butt to the opposite cut edge. Avoid adhesive contact with the top of the carpet nap.

Soap and water, safety solvent or mineral spirits.

# 6. AVAILABILITY

TEC premium surface preparation, tile, stone, carpet, wood and resilient floor covering installation products are available nationwide. To locate TEC® products in your area, please contact:

Phone: 800-832-9002 Website: tecspecialty.com

# 7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. TEC Specialty Products LLC disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product. For Limited Warranty details visit tecspecialty.com. To obtain a hard copy of the Limited Warranty call TEC Specialty Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

# 8. MAINTENANCE

Not applicable

#### 9. TECHNICAL SERVICES

# **Technical and safety literature**

To acquire technical and safety literature. please visit our website at tecspecialty.com.

# 10. FILING SYSTEM

Division 9

# To learn more, visit TECspecialty.com



TEC Specialty Products LLC | 1105 South Frontenac Street, Aurora, IL 60504-6451





(O) tecinstallationsystems



▼ TECInstallationSystems



**TEC Installation Systems**