



Level Set® Reinforcing Fibers

Created September 2025

1. PRODUCT NAME

TEC® Level Set® Reinforcing Fibers

2. MANUFACTURER

TEC Specialty Products LLC
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.832.9002 Customer Service
800.832.9023 Technical Support
tecspecialty.com

3. DESCRIPTION

TEC Level Set Reinforcing Fibers can significantly enhance the performance and durability of self-leveling underlayments by increasing tensile and flexural strength and reducing shrinkage and crack formation. Level Set Reinforcing Fibers can eliminate the need for lath for wood subfloors thereby speeding up installation while reducing labor and material costs.

Key Features and Benefits

- Use with TEC® Level Set® 500 HF, 400 HF, 350 and 300 self-leveling underlayments
- No reinforcement mesh required over wood substrates when used as directed
- Ideal for wood frame and multifamily construction
- Easy mixing: 1 bag of fibers per 1 bag of self-leveling underlayment
- Reduces shrinkage and cracking
- Increases tensile and flexural strength
- Made from recycled content

Packaging

24 (125 gram) plastic bags per case (3.0 kg) Product #10019174

Coverage

1 bag = 125 g of reinforcing fibers per bag of self-leveling compound

Suitable Substrates

Interior use only. See TEC SLU Product Data Sheet for substrate information.

Storage

Store in a cool, dry area.

Shelf Life

Maximum of 2 years from date of manufacture in unopened package.

Limitations

- For interior use only.

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC brand product(s) under normal environmental and working conditions. Because each project is different, TEC Specialty Products LLC cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Physical Properties

Description	
Packaging	Plastic Bag
Color	White
Alkali Resistance	High
Storage	Store in a cool, dry area.
Shelf Life	Maximum of 2 year from date of manufacture in unopened package.

5. INSTALLATION INSTRUCTIONS

Mixing

Use 1 bag of TEC Level Set Reinforcing Fibers per bag of SLU. Minimum pour depth with fibers is $\frac{3}{8}$ " inch (9.5 mm). Add TEC Self-Leveling Reinforcing Fibers to the mix water before adding the SLU while mixing at full speed. Mix until fibers are dispersed then add the SLU and mix according to the product instructions.

6. AVAILABILITY

TEC premium surface preparation, tile, stone, carpet, wood and resilient floor covering installation products are available nationwide. To locate TEC products in your area, please contact:

Phone: 800-832-9002

Website: tecspecially.com

7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **TEC Specialty Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit tecspecially.com. To obtain a hard copy of the Limited Warranty call TEC Specialty Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical and safety literature

To acquire technical and safety literature, please visit our website at tecspecially.com.

10. FILING SYSTEM

Divisions 3 and 9



To learn more, visit [TECspecially.com](https://www.tecspecially.com)



TEC Specialty Products LLC | 1105 South Frontenac Street, Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems