

When Quick Turnarounds Count



TEC® Level Set® 300 Self-Leveling Underlayment



Ideal for quick turnarounds, TEC® Level Set® 300 allows you to quickly smooth substrates without sacrificing performance. This high quality, calcium aluminate-based, self-leveling underlayment provides you with a flat, extremely smooth and durable surface that is **walkable in 2-3 hours**. And, you can install moisture-sensitive floor coverings in as little as 16-24 hours.

Contact your local sales rep to request a demo. Have a question? Visit TECQuestions.com.



To learn more, visit TECSpecialty.com

See Reverse for More Information



Level Set® 300 Self-Leveling Underlayment

Ideal for fast track applications, TEC® Level Set® 300 is a high-performance, calcium aluminate-based, self-leveling underlayment that provides a flat, extremely smooth, and strong, durable surface for finished flooring installation. It is pourable or pumpable for interior applications, offers exceptional workability for an ultra-smooth surface, is walkable in 2-3 hours, can be applied up to 2" (50 mm) neat in single applications and be featheredged to adjoining elevations. For details about TEC® product or system warranties, contact your sales associate or visit tecspecialty.com.



Exceptional workability for an ultra-smooth surface



Pourable or pumpable for interior applications



Install moisture sensitive floor covering in 16-24 hours

Features and Benefits

- Formulated for fast-track applications – walkable in 2-3 hours
- Up to 2" (50 mm) neat and can be featheredged to adjoining elevations
- Applied up to 5" (12 cm) with proper aggregate
- High compressive strength - 5,500 psi (38.0 MPa)
- Accepts non-moisture sensitive tile and stone in 4 hours
- Contributes to LEED® project points
- Zero VOC

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Depth	Approximate Coverage per 50 lbs. (22.68 kg)
1/8" (3 mm)	50 sq. ft. (4.65 m²)
1/4" (6 mm)	25 sq. ft. (2.32 m²)
1/2" (12 mm)	12.5 sq. ft. (1.16 m²)
1" (25 mm)	6.25 sq. ft. (0.58 m²)
2" (50 mm)	3.125 sq. ft. (0.29 m²)

Packaging

50 lb. plastic bags (22.68 kg)

50 lb. moisture-resistant bags (22.68 kg)

Product #15030023

Product #15036050

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Pavers
- Cement backerboard
- 3/4" hardwood flooring
- Exterior grade plywood (with reinforcement lath)
- Gypsum substrates—minimum tensile bond strength 72 psi (0.5 MPa)
- Ceramic, porcelain or quarry tile
- Cement or epoxy terrazzo
- Metal
- VCT or full glued down, non-cushioned vinyl sheetgoods
- Oriented Strand Board (OSB) (with reinforcement lath)

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Gray
Working Time	25-35 minutes
Walkable	2-3 hours
Flooring Installation	Tile: 3-4 hours Moisture sensitive: 16-24 hours
Flow (ASTM C1708)	5"-6" (12.7-15.2 cm)
Storage	Store in cool, dry area away from direct sunlight. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.



Conforms with LEED v4 low emitting interiors.
Compliant with (CDPH) Standard Method v1.2 VOC Emissions.

To learn more, visit TECSpecialty.com



TEC Specialty Products LLC | 1105 South Frontenac Street, Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems