

A Feather-Smooth Surface Prep Solution

See Reverse for
More Information ▶



TEC® Feather Edge Skim Coat

This fast-set solution offers exceptional performance and bond strength to effortlessly transition surface areas and smooth, skim coat and level substrate irregularities. It is an excellent choice for most substrates and it provides a suitable surface for even the most demanding floor coverings, such as VCT and sheet vinyl. This proven product allows installation of most floor coverings in as little as 15-20 minutes.

Contact your local sales rep to request a demo. Have a question? Visit TECQuestions.com.



TECSpecialty.com



@InstallwithTEC



TECInstallationSystems



TEC Installation Systems





Feather Edge Skim Coat

TEC® Feather Edge Skim Coat is a high-quality, cement-based compound designed to skim coat, smooth and level irregularities from featheredge up to ½" (12mm). It has exceptional bond strength, and rapidly sets in as little as 15-20 minutes for installing most floor coverings, with exceptional performance. Excellent for use over most substrates, it provides a suitable surface for even the most demanding floor coverings, such as VCT and sheet vinyl. For most applications, use of a primer is not required. For more information, see the Product Data Sheet, located at tecspecialty.com. For details about TEC® product or system warranties, contact your sales associate or visit tecspecialty.com.



Fast setting - install most flooring in as soon as 15-20 minutes



Featheredge up to a ½" (12 mm)



Skim coat irregularities

Features and Benefits

- Fast setting - install flooring in as soon as 15-20 minutes
- Featheredge up to ½" (12 mm)
- Exceptional bond strength
- Sandable
- Contributes to LEED® project points
- Zero VOC

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Cement backerboards
- Concrete terrazzo
- Ceramic tile, pavers, brick*
- Quarry tile
- Epoxy terrazzo
- Exterior grade plywood, C-C (plugged) or better
- Exterior grade lauan plywood—Type I Trademarked Exterior Grade, OVL, CC, BB.OVL face grades only
- Vinyl composition tile (VCT), embossed resilient floor coverings—must be bonded well to an approved substrate and be single layer.*
- Adhesive residue (except tacky or pressure-sensitive adhesive)*
- Gypsum substrates** - minimum tensile bond strength 72 psi (0.5 MPa)

*Prime substrate with TEC® Multipurpose Primer or mix with TEC® Patch Additive.

**Requires priming with TEC® Multipurpose Primer.

Packaging

10 lb. plastic bags (4.54 kg)

Product #3303863311



Conforms with LEED v4 low emitting interiors.
Compliant with (CDPH) Standard Method v1.2 VOC Emissions.

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Depth	Approximate Coverage per 10 lbs. (4.54 kg)
⅛" (3 mm)	30-36 sq. ft. (2.8-3.3 m²)
¼" (6 mm)	15-18 sq. ft. (1.4-1.7 m²)
½" (12 mm)	7.5-9 sq. ft. (0.7-0.8 m²)
Embossing	300-500 sq. ft. (27.9-46.5 m²)

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Gray
Compressive Strength (ASTM C109)	3600 psi (24.6 MPa)
Pot Life	15-20 minutes
Install Floor Covering*	15-60 minutes
Storage	Store away from direct sunlight in a well-ventilated, cool, dry area. If storing after opening, remove all air from container and seal tightly.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.

*Flooring installation after application is dependent on thickness, drying conditions, and type of flooring.

To learn more, visit TECSpecialty.com



TEC Specialty Products LLC | 1105 South Frontenac Street, Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems