

# The Finishing Touch For Your Tile Job

See Reverse for  
More Information ▶

## TEC® AccuColor 100® 100% Silicone Sealant



A tile installation isn't complete without the caulk or sealant. AccuColor 100® 100% Silicone Sealant is a high-performance, flexible sealant that's applied at tiled wall intersections and at changes of plane to create a water-resistant seal. Ideal for water-exposed areas, such as swimming pools, spas, showers and tubs, the time-tested 100% silicone sealant is UV-resistant, won't discolor or shrink, and color matches all 32 popular TEC® grout colors, plus is offered in clear.

**Reach for AccuColor 100® for a flawless finish.**





## AccuColor 100® 100% Silicone Sealant

TEC® AccuColor 100® 100% Silicone Sealant is easy to use, flexible, and non corrosive. This high-performance sealant resists water and most common chemicals, offers permanent flexibility, won't crack, shrink or sag and provides excellent weatherability. Use for fountains, spas, showers, tubs, swimming pools and other wet area applications. For details about TEC® product or system warranties, contact your sales associate or visit [tecspecialty.com](http://tecspecialty.com).



Recommended for fountains, spas, showers, tubs, pools and other wet areas.

### Features and Benefits

- Ideal for use where TCNA EJ171 installation method is required
- Meets ASTM C920 Type S, NS, Class 50; TT-S-00230C (COM-NBS); TT-S-01543A (COM-NBS); MIL-A-46106A; AAMA 808.3, 805.2, 803.3 (Type I), 802.3 (Type II)
- Non-sagging, single component with 50% total joint movement
- UV light won't break down, discolor or shrink product
- Excellent weatherability, long life and water resistant seal
- Permanent flexibility and durability, won't crack or soften
- Easy to use, non-corrosive, neutral curing product
- Low odor, ideal for use in confined work areas
- Low VOC; contributes to LEED® project points
- Available in clear plus 32 colors—matches TEC® standard grout colors

### Suitable Substrates

- Natural stone
- Metals
- Porcelain
- Plastic surfaces
- Glass
- Ceramic/masonry
- Wood

### Packaging

10.5 fl. oz. cartridge (310 mL)

### Coverage

Figures shown in the chart are presented only as guidelines. Coverage will vary with application and bead size.

Bead Size	Approximate Coverage per 10.5 fl. oz. Cartridge (310 mL)
3/16" (4.7 mm)	50 lineal feet (15.2 lineal meter)
1/4" (6 mm)	25 lineal feet (7.6 lineal meter)

### Technical Data

#### Physical Properties

Description	
Physical State	Soft Paste
Color	32 pigmented colors, 1 clear
Odor	Nil
Open Time [at 72°F (22°C)]	10 minutes
Final Cure	1 day, 14 days for swimming pool applications
Foot Traffic Rating (ASTM C627)	Residential
VOC	40 g/L
Freeze/Thaw Stability	Freeze/thaw stable. If frozen, slowly bring material back to room temperature.
Storage	Store in cool, dry location. Do not store open containers.
Shelf Life	Maximum 24 months from date of manufacture in properly stored, unopened package.

To learn more, visit [TECSpecialty.com](http://TECSpecialty.com)



TEC Specialty Products LLC | 1105 South Frontenac Street, Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems