

SAFETY DATA SHEET**Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE**

Version 1.0

Revision Date 09/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE
Product code : 100000019234

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac
Aurora, IL, 60504

Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours) : 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Isocyanate based product, Polyurethane resin

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	paste
Color	light yellow
Odor	characteristic

GHS Classification

Skin irritation : Category 2
Eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

SAFETY DATA SHEET**Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE**

Version 1.0

Revision Date 09/10/2025

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection. P285 In case of inadequate ventilation wear respiratory protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. P362 Take off contaminated clothing and wash before reuse.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Aggravated Medical Condition : None known.
Symptoms of Overexposure : Breathing difficulties

Carcinogenicity:**IARC**

Group 1: Carcinogenic to humans During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.
Quartz (SiO₂) 14808-60-7

OSHA**NTP**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
Known to be human carcinogen During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.
Quartz (SiO₂) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Calcium carbonate	471-34-1	50 - 70
Isocyanate Based Polymer	9048-57-1	10 - 20
glass, oxide, chemicals, non-fibrous	65997-17-3	1 - 5
Sodium borosilicate	50815-87-7	1 - 5

SAFETY DATA SHEET

Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE

Version 1.0

Revision Date 09/10/2025

4,4'-Methylenediphenyl diisocyanate	101-68-8	1 - 5
Quartz (SiO ₂)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. If symptoms persist, call a physician.
In case of skin contact	: Get medical attention if irritation develops and persists. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use.
In case of eye contact	: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	: Do not induce vomiting. If conscious, give 2 glasses of water. Get immediate medical attention.
Most important symptoms and effects, both acute and delayed	: Breathing difficulties Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Specific hazards during fire fighting	: Burning produces irritant fumes.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE

Version 1.0

Revision Date 09/10/2025

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
Shovel into suitable container for disposal.
Neutralize with the following product(s):
Ammonia

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Protect from moisture.
Avoid inhalation, ingestion and contact with skin and eyes.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m ³	CAL PEL
		PEL (respirable dust fraction)	5 mg/m ³	CAL PEL
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
glass, oxide, chemicals, non-fibrous	65997-17-3	TWA	1 fibres per cubic centimeter	ACGIH
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA	1 fibres per cubic centimeter	ACGIH
		TWA (fibers)	1 fibres per cubic centimeter	ACGIH
		TWA (fibers)	1 fibres per cubic centimeter	ACGIH
4,4'-Methylenediphenyl	101-68-8	TWA	0.005 ppm	ACGIH

SAFETY DATA SHEET

Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE

Version 1.0

Revision Date 09/10/2025

diisocyanate				
		C	0.02 ppm 0.2 mg/m3	OSHA Z-1
		C	0.2 ppm 0.2 mg/m3	NIOSH REL
		TWA	0.005 ppm	ACGIH
		C	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	NIOSH REL
		PEL	0.005 ppm 0.051 mg/m3	CAL PEL
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
Quartz (SiO ₂)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SAFETY DATA SHEET

Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE

Version 1.0

Revision Date 09/10/2025

Hand protection	
Material	: Nitrile rubber
Eye protection	: Safety glasses with side-shields
Hygiene measures	: Avoid contact with skin, eyes and clothing. Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Color	: light yellow
Odor	: characteristic
Odor Threshold	: no data available
pH	: Not applicable
Melting point/freezing point	: is not determined
Initial boiling point and boiling range	: is not determined
Flash point	: 100 °CMethod: closed cupNot applicable
Evaporation rate	: is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Vapor pressure	: is not determined
Density	: 1.27 g/cm3
Solubility(ies)	
Water solubility	: is not determined
Partition coefficient: n-octanol/water	: no data available
Autoignition temperature	: is not determined
Viscosity	
Viscosity, kinematic	: is not determined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.
Chemical stability	: The product is chemically stable.

SAFETY DATA SHEET**Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE**

Version 1.0

Revision Date 09/10/2025

Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Incompatible materials	: Amines Strong acids and strong bases
Hazardous decomposition products	: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute inhalation toxicity	: Acute toxicity estimate : 72.86 mg/l Exposure time: 4 Hours Test atmosphere: dust/mist Method: Calculation method
---------------------------	--

Components:**4,4'-Methylenediphenyl diisocyanate:**

Acute inhalation toxicity	: Acute toxicity estimate : 1.5 mg/l Test atmosphere: dust/mist Method: Expert judgment
---------------------------	---

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

SAFETY DATA SHEET

Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE

Version 1.0

Revision Date 09/10/2025

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET**Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE**

Version 1.0

Revision Date 09/10/2025

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

4,4'-Methylenediphenyl diisocyanate	101-68-8
Polymethylene polyphenyl isocyanate	9016-87-9

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

4,4'-Methylenediphenyl diisocyanate	101-68-8
-------------------------------------	----------

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:**TSCA**

All substances listed as active on the TSCA inventory

DSL

All components of this product are on the Canadian DSL

Please reach out to TEC Specialty Products LLC for further information regarding chemical inventories not listed above. **Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET


Fortane™ LD POLYURETHANE WOOD FLOOR ADHESIVE

Version 1.0

Revision Date 09/10/2025

Further information

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic