

Fortane SL-HF PW

Version 1.0 Revision Date 09/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Fortane SL-HF PW Product code : 100000033722

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours): 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Cement, Adhesive

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	powder
Color	brown
Odor	characteristic

GHS Classification

Skin irritation : Category 2
Serious eye damage : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 1A
Specific target organ toxicity - Category 1

repeated exposure

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye



Fortane SL-HF PW

Version 1.0

Revision Date 09/10/2025

damage. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
quartz (SiO2)	14808-60-7	30 - 50
Cement, alumina, chemicals	65997-16-2	10 - 20
Calcium carbonate	471-34-1	10 - 20
Limestone	1317-65-3	10 - 20
Cement, portland, chemicals	65997-15-1	10 - 20
calcium sulfate	7778-18-9	5 - 10

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.



Fortane SL-HF PW

Version 1.0 Revision Date 09/10/2025

If inhaled : If inhaled Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Oxygen or artificial respiration if needed.

In case of skin contact : Wash off with soap and water.

Remove contaminated clothing. If irritation develops, get

medical attention.

: Flush eyes with water at least 15 minutes. Get medical In case of eye contact

attention if eye irritation develops or persists.

: Do not induce vomiting. Seek medical attention if symptoms If swallowed

develop. Provide medical care provider with this SDS.

If conscious, drink plenty of water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure.

SECTION 5. FIRE-FIGHTING MEASURES

: Use water spray, alcohol-resistant foam, dry chemical or Suitable extinguishing media

carbon dioxide.

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

No hazardous combustion products are known

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

methods

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.



Fortane SL-HF PW

Version 1.0 Revision Date 09/10/2025

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Should not be released into the environment.

Methods and materials for containment and cleaning up

Use approved industrial vacuum cleaner for removal.
 Do not use compressed air for cleaning purposes.
 Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid creating dust.

Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Take precautionary measures against static discharges. Provide for appropriate exhaust ventilation and dust collection

at machinery.

Conditions for safe storage : Keep tightly closed in a dry and cool place.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA	250 mppcf	OSHA Z-3



Fortane SL-HF PW

Version 1.0

Revision Date 09/10/2025

I	I	(reenirable)	/ 0/ S:O2 · F	1
		(respirable) TWA	/ %SiO2+5	NIOSH REL
		(Respirable	0.05 mg/m3	INIOSH KEL
		dust)		
		TWA	0.1 mg/m3	OSHA P0
			0.1 mg/m3	USHA PU
		(Respirable		
		fraction)	0.05/0	00114.7.4
		TWA	0.05 mg/m3	OSHA Z-1
		(Respirable		
		dust)		
		PEL	0.05 mg/m3	CAL PEL
		(Respirable		
		dust)		
		TWA	0.1 mg/m3	OSHA P0
		(respirable		
		dust fraction)		
Calcium carbonate	471-34-1	PEL (Total	10 mg/m3	CAL PEL
		dust)		
		PEL	5 mg/m3	CAL PEL
		(respirable		
		dust fraction)		
		TWA	5 mg/m3	NIOSH REL
		(Respirable)	o mg/mo	100111122
		TWA (total)	10 mg/m3	NIOSH REL
Limestone	1317-65-3	TWA	5 mg/m3	NIOSH REL
Limestone	1317-03-3	(Respirable)	5 mg/ms	MOSHIKEL
		TWA (total)	10 mg/m3	NIOSH REL
				OSHA Z-1
		TWA (total dust)	15 mg/m3	USHA Z-1
			F	00114.7.4
		TWA	5 mg/m3	OSHA Z-1
		(respirable		
		fraction)		
		TWA (Total)	15 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(Respirable		
		fraction)		
		TWA (Total	15 mg/m3	OSHA P0
		dust)		
		TWA	5 mg/m3	OSHA P0
		(respirable		
		dust fraction)		
Cement, portland, chemicals	65997-15-1	TWA	1 mg/m3	ACGIH
, ,		(Respirable		
		particulate		
		matter)		
		TWA (total	15 mg/m3	OSHA Z-1
		dust)	109,0	33.7.2
		TWA	5 mg/m3	OSHA Z-1
		(respirable	J mg/ms	0011/12-1
		fraction)		
		i i action)	<u> </u>	1



Fortane SL-HF PW

Version 1.0

Revision Date 09/10/2025

	<u>.</u>			
		TWA (Dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Respirable fraction)	5 mg/m3	OSHA P0
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
calcium sulfate	7778-18-9	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total)	15 mg/m3	OSHA P0
		TWA (Respirable fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		PEL (Total dust)	10 mg/m3	CAL PEL
_		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate	0.025 mg/m3	ACGIH



Fortane SL-HF PW

Version 1.0 Revision Date 09/10/2025

matter)		
TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
PEL (Respirable dust)	0.05 mg/m3	CAL PEL
TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management

measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within

recommended exposure guidelines.

Filter type : Particulates type

Hand protection

Material : butyl-rubber

Eye protection : Safety glasses with side-shields

Skin and body protection : Long sleeved clothing

Remove and wash contaminated clothing before re-use.

Skin should be washed after contact.

Protective measures : Avoid contact with skin.

Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder



Fortane SL-HF PW

Version 1.0 Revision Date 09/10/2025

Color : brown

Odor : characteristic Odor Threshold : no data available

: is not determined

: is not determined

Flash point : is not determined : Not applicable Evaporation rate

: Upper flammability limit Upper explosion limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

: 120 lb/ft3 Density

Solubility(ies)

Water solubility : is not determined Partition coefficient: n-: Not applicable

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.

Hazardous decomposition products

: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available



Fortane SL-HF PW

Version 1.0 Revision Date 09/10/2025

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components: calcium sulfate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,970 mg/l

Exposure time: 96 Hours

Method: static test

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : To the best of our knowledge, this product does not meet the

definition of hazardous waste under the U.S. EPA Hazardous



Forta	nn	CI		\mathbf{D}	V
רטו נס	11 IC	J		L A	v

Version 1.0

Revision Date 09/10/2025

Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more

restrictive requirements.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

Clean Air Act



Fortane SL-HF PW

Version 1.0

Revision Date 09/10/2025

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

US State Regulations

California Prop 65

Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA

All substances listed as active on the TSCA inventory


All components of this product are on the Canadian DSL

Please reach out to TEC Specialty Products LLC for further information regarding chemical inventories not listed above. Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AllC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic