

STRONG, SILENT, SIMPLY PERFECT.

Advanced adhesive technology
for comfort and durability.



Wood Perfect™ Moisture & Sound Control Adhesive

Strong, silent, and built to last — TEC® Wood Perfect™ is the all-in-one adhesive that delivers powerful bonding, sound control, and lasting durability. Easy to trowel and engineered for performance, it's the perfect foundation for beautiful wood floors. So you can work smarter, not harder on your next wood floor installation.



Visit [TECspecialty.com](https://www.tecspecialty.com)



Wood Perfect™ Moisture & Sound Control Adhesive



No preinstallation moisture testing



Easy trowelling with superior ridge retention



Fast-setting, high tack formulation

Use With

- Engineered wood • Solid wood • Parquet • Acoustic Underlayments

Features and Benefits



Moisture Control



Easy Troweling & Excellent Ridge Retention



Superior Sound Control

ADDITIONAL FEATURES AND BENEFITS

- Superior adhesion
- No pre-installation testing necessary
- Excellent ridge retention
- Aggressive green grab and robust adhesion
- Ideal for all types of wood flooring
- Fast curing

Coverage

Determine recommended trowel size based on flooring type. Coverage will vary with the absorption of substrate and trowel size. Figures below are presented only as guidelines.

Flooring Type	Recommended Trowel Size	Approximate Coverage
Glue Down Only Method		
5/16" (8 mm) Fingerblock Parquet	1/8" x 1/8" x 1/8" (3.2 x 3.2 x 3.2 mm) Square-notch trowel	55-65 ft ² /gal. (1.35-1.60 m ² /L)
Engineered Plank or bamboo 1/2" (12.7 mm) or less and less than 7" (178 mm) wide	3/16" x 1/4" x 1/2" (4.8 x 6.4 x 12.7 mm) V-notch trowel	60-70 ft ² /gal. (1.47-1.72 m ² /L)
Engineered Plank or bamboo thicker than 1/2" (12.7 mm) or 7" (178 mm) or wider	3/16" x 3/16" x 3/16" (4.8 x 4.8 x 4.8 mm) Square-notch trowel	35-45 ft ² /gal. (0.86-1.10 m ² /L)
Solid Wood Plank, shorts or plywood	1/4" x 1/4" x 1/4" (6.4 x 6.4 x 6.4 mm) Square-notch trowel	30-40 ft ² /gal. (0.74-0.98 m ² /L)
Moisture Control Method		
Parquet, engineered or solid plank or bamboo	1/4" x 1/4" (6.4 x 6.4 mm) V-notch trowel	30-35 ft ² /gal. (0.74-0.86 m ² /L)
For Use With Acoustic Underlayment		
Crumb rubber or cork underlayment	1/16" x 1/16" x 1/16" (1.6 x 1.6 x 1.6 mm) Square-notch trowel	85-95 ft ² /gal. (2.09-2.33 m ² /L)

Technical Data

Physical Properties

Description		Description	
VOC Content	<100 grams/Liter	Application Temperature	65°-95°F (18°-35°C)
Wood Perfect meets all SCAQM district requirements		Traffic Restrictions	Foot traffic after 8 hours; heavy traffic after 24 hours
Consistency	Creamy liquid	Open Time	Up to 45 minutes, depending on ambient conditions
Color	Light tan	Freeze/Thaw Stability	Store above 40°F (4.4°C) in a cool, dry location
Trowelability	Smooth	Acoustical Data	IIC - 69 dB
Shelf Life	One year in unopened container		STC - 66 dB
Storage	40°-95°F (4.4°-35°C) in a cool, dry location		IIC - 52 (No drop ceiling)

Packaging

4 gallon plastic pail (15.13 L)

Product # 10018787

For details about TEC® product or system warranties, contact your sales associate or visit tecspecialty.com.



Scan for Online Coverage Calculator

To learn more, visit tecspecialty.com



TEC Specialty Products LLC
1105 South Frontenac Street
Aurora, IL 60504-6451



TECInstallationSystems



@tecinstallationsystems



TECInstallationSystems



TEC Installation Systems

©Copyright 2025 TEC Specialty Products LLC
TEC®, the TEC® logo and Wood Perfect™ are trademarks
of TEC Specialty Products LLC

SSWP_N1025-16