

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TEC® POWER GROUT® 550-969 COFFEE  
Product code : 100000015255

##### Manufacturer or supplier's details

Company : TEC Specialty Products  
Address : 1105 South Frontenac  
Aurora, IL, 60504  
Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours) : 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

##### Recommended use of the chemical and restrictions on use

Recommended use : Cement, Adhesive

#### SECTION 2. HAZARDS IDENTIFICATION

##### Emergency Overview

|            |          |
|------------|----------|
| Appearance | powder   |
| Color      | brown    |
| Odor       | odorless |

##### GHS Classification

Skin irritation : Category 2  
Serious eye damage : Category 1  
Carcinogenicity : Category 1A  
Specific target organ toxicity - repeated exposure : Category 1

##### GHS label elements

Hazard pictograms :  

Signal Word : Danger

##### Hazard Statements:

H315 Causes skin irritation. H318 Causes serious eye damage. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

#### Precautionary Statements:

**Prevention:** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

**Storage:** P405 Store locked up.

**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

#### Potential Health Effects

#### Carcinogenicity:

##### IARC

Group 1: Carcinogenic to humans

quartz (SiO<sub>2</sub>) 14808-60-7

Quartz (SiO<sub>2</sub>) 14808-60-7

##### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

##### NTP

Known to be human carcinogen

quartz (SiO<sub>2</sub>) 14808-60-7

Quartz (SiO<sub>2</sub>) 14808-60-7

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous ingredients

| Chemical name              | CAS-No.    | Concentration [%] |
|----------------------------|------------|-------------------|
| Cement, alumina, chemicals | 65997-16-2 | 30 - 50           |
| quartz (SiO <sub>2</sub> ) | 14808-60-7 | 30 - 50           |
| plaster of Paris           | 26499-65-0 | 5 - 10            |
| Calcium carbonate          | 471-34-1   | 5 - 10            |
| Limestone                  | 1317-65-3  | 5 - 10            |
| Titanium dioxide           | 13463-67-7 | 1 - 5             |
| Quartz (SiO <sub>2</sub> ) | 14808-60-7 | 0.1 - 1           |

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

|                                                             |                                                                                                                                                                                                                      |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice                                              | : In the case of accident or if you feel unwell, seek medical advice immediately.                                                                                                                                    |
| If inhaled                                                  | : If inhaled<br>Remove person to fresh air. If signs/symptoms continue, get medical attention.<br>Oxygen or artificial respiration if needed.                                                                        |
| In case of skin contact                                     | : Wash off with soap and water.<br>Remove contaminated clothing. If irritation develops, get medical attention.                                                                                                      |
| In case of eye contact                                      | : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.                                                                                                           |
| If swallowed                                                | : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.<br>If conscious, drink plenty of water.<br>Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : Causes skin irritation.<br>Causes serious eye damage.<br>May cause cancer.<br>Causes damage to organs through prolonged or repeated exposure.                                                                      |

#### SECTION 5. FIRE-FIGHTING MEASURES

|                                                |                                                                                                                                                                                                                 |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.                                                                                                                                      |
| Unsuitable extinguishing media                 | : None known.                                                                                                                                                                                                   |
| Specific hazards during fire fighting          | : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.<br>No hazardous combustion products are known |
| Hazardous combustion products                  | : No hazardous combustion products are known                                                                                                                                                                    |
| Specific extinguishing methods                 | :                                                                                                                                                                                                               |
| Further information                            | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                       |
| Special protective equipment for fire-fighters | : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.                                                                                             |

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.  
Should not be released into the environment.
- Methods and materials for containment and cleaning up : Use approved industrial vacuum cleaner for removal.  
Do not use compressed air for cleaning purposes.  
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

#### SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid creating dust.  
Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.  
Take precautionary measures against static discharges.  
Provide for appropriate exhaust ventilation and dust collection at machinery.
- Conditions for safe storage : Keep tightly closed in a dry and cool place.
- Materials to avoid : No special restrictions on storage with other products.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Ingredients with workplace control parameters

| Components                 | CAS-No.    | Value type<br>(Form of exposure)       | Control parameters /<br>Permissible concentration | Basis    |
|----------------------------|------------|----------------------------------------|---------------------------------------------------|----------|
| quartz (SiO <sub>2</sub> ) | 14808-60-7 | TWA<br>(Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                           | ACGIH    |
|                            |            | TWA (total dust)                       | 30 mg/m <sup>3</sup><br>/ %SiO <sub>2</sub> +2    | OSHA Z-3 |
|                            |            | TWA<br>(respirable)                    | 10 mg/m <sup>3</sup><br>/ %SiO <sub>2</sub> +2    | OSHA Z-3 |

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

|                   |            |                                |                                  |           |
|-------------------|------------|--------------------------------|----------------------------------|-----------|
|                   |            | TWA (respirable)               | 250 mppcf / %SiO <sub>2</sub> +5 | OSHA Z-3  |
|                   |            | TWA (Respirable dust)          | 0.05 mg/m <sup>3</sup>           | NIOSH REL |
|                   |            | TWA (Respirable fraction)      | 0.1 mg/m <sup>3</sup>            | OSHA P0   |
|                   |            | TWA (Respirable dust)          | 0.05 mg/m <sup>3</sup>           | OSHA Z-1  |
|                   |            | PEL (Respirable dust)          | 0.05 mg/m <sup>3</sup>           | CAL PEL   |
|                   |            | TWA (respirable dust fraction) | 0.1 mg/m <sup>3</sup>            | OSHA P0   |
| plaster of Paris  | 26499-65-0 | TWA (Respirable)               | 5 mg/m <sup>3</sup>              | NIOSH REL |
|                   |            | TWA (total)                    | 10 mg/m <sup>3</sup>             | NIOSH REL |
|                   |            | TWA (total dust)               | 15 mg/m <sup>3</sup>             | OSHA Z-1  |
|                   |            | TWA (respirable fraction)      | 5 mg/m <sup>3</sup>              | OSHA Z-1  |
|                   |            | TWA (Total dust)               | 15 mg/m <sup>3</sup>             | OSHA P0   |
|                   |            | TWA (respirable dust fraction) | 5 mg/m <sup>3</sup>              | OSHA P0   |
|                   |            | PEL (Total dust)               | 10 mg/m <sup>3</sup>             | CAL PEL   |
|                   |            | PEL (respirable dust fraction) | 5 mg/m <sup>3</sup>              | CAL PEL   |
| Calcium carbonate | 471-34-1   | PEL (Total dust)               | 10 mg/m <sup>3</sup>             | CAL PEL   |
|                   |            | PEL (respirable dust fraction) | 5 mg/m <sup>3</sup>              | CAL PEL   |
|                   |            | TWA (Respirable)               | 5 mg/m <sup>3</sup>              | NIOSH REL |
|                   |            | TWA (total)                    | 10 mg/m <sup>3</sup>             | NIOSH REL |
| Limestone         | 1317-65-3  | TWA (Respirable)               | 5 mg/m <sup>3</sup>              | NIOSH REL |
|                   |            | TWA (total)                    | 10 mg/m <sup>3</sup>             | NIOSH REL |
|                   |            | TWA (Respirable)               | 5 mg/m <sup>3</sup>              | NIOSH REL |
|                   |            | TWA (total)                    | 10 mg/m <sup>3</sup>             | NIOSH REL |
|                   |            | TWA                            | 5 mg/m <sup>3</sup>              | NIOSH REL |

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

|                  |            |                                     |                     |           |
|------------------|------------|-------------------------------------|---------------------|-----------|
|                  |            | (Respirable)                        |                     |           |
|                  |            | TWA (total)                         | 10 mg/m3            | NIOSH REL |
|                  |            | TWA (total dust)                    | 15 mg/m3            | OSHA Z-1  |
|                  |            | TWA (respirable fraction)           | 5 mg/m3             | OSHA Z-1  |
|                  |            | TWA (Total)                         | 15 mg/m3            | OSHA P0   |
|                  |            | TWA (Respirable fraction)           | 5 mg/m3             | OSHA P0   |
|                  |            | TWA (Total dust)                    | 15 mg/m3            | OSHA P0   |
|                  |            | TWA (respirable dust fraction)      | 5 mg/m3             | OSHA P0   |
| Titanium dioxide | 13463-67-7 | TWA                                 | 10 mg/m3            | ACGIH     |
|                  |            | TWA (total dust)                    | 15 mg/m3            | OSHA Z-1  |
|                  |            | TWA (Total)                         | 10 mg/m3            | OSHA P0   |
|                  |            | TWA (Total dust)                    | 10 mg/m3            | OSHA P0   |
|                  |            | TWA (Respirable particulate matter) | 0.2 mg/m3           | ACGIH     |
|                  |            | TWA (Respirable particulate matter) | 2.5 mg/m3           | ACGIH     |
| Quartz (SiO2)    | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m3         | ACGIH     |
|                  |            | TWA (total dust)                    | 30 mg/m3 / %SiO2+2  | OSHA Z-3  |
|                  |            | TWA (respirable)                    | 10 mg/m3 / %SiO2+2  | OSHA Z-3  |
|                  |            | TWA (respirable)                    | 250 mppcf / %SiO2+5 | OSHA Z-3  |
|                  |            | TWA (Respirable fraction)           | 0.1 mg/m3           | OSHA P0   |
|                  |            | TWA (Respirable dust)               | 0.05 mg/m3          | OSHA Z-1  |
|                  |            | PEL (Respirable dust)               | 0.05 mg/m3          | CAL PEL   |
|                  |            | TWA                                 | 0.1 mg/m3           | OSHA P0   |

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

|  |  |                               |  |  |
|--|--|-------------------------------|--|--|
|  |  | (respirable<br>dust fraction) |  |  |
|--|--|-------------------------------|--|--|

**Engineering measures** : Use local exhaust ventilation or other engineering controls to minimize exposures.

#### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

**Filter type** : Particulates type

**Hand protection**  
**Material** : butyl-rubber

**Eye protection** : Safety glasses with side-shields

**Skin and body protection** : Long sleeved clothing  
Remove and wash contaminated clothing before re-use.  
Skin should be washed after contact.

**Protective measures** : Avoid contact with skin.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : powder  
**Color** : brown  
**Odor** : odorless  
**Odor Threshold** : no data available  
: is not determined  
: is not determined  
**Flash point** : is not determined  
**Evaporation rate** : Not applicable  
**Upper explosion limit** : Upper flammability limit  
is not determined  
**Lower explosion limit** : Lower flammability limit  
is not determined  
**Density** : 11.0 lb/gal  
**Solubility(ies)**  
**Water solubility** : is not determined

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : is not determined

Viscosity  
Viscosity, kinematic : Not applicable

#### SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Hazardous polymerization does not occur.

Hazardous decomposition products : No decomposition if stored and applied as directed.

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Acute toxicity

No data available

##### Skin corrosion/irritation

No data available

##### Serious eye damage/eye irritation

No data available

##### Respiratory or skin sensitization

No data available

##### Germ cell mutagenicity

No data available

##### Carcinogenicity

No data available

##### Reproductive toxicity

No data available

##### STOT-single exposure

No data available

##### STOT-repeated exposure

No data available

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

#### Aspiration toxicity

No data available

## SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

#### Mobility in soil

No data available

#### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

## SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SAFETY DATA SHEET

### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

**SARA 311/312 Hazards** : Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### US State Regulations

**California Prop 65** Please contact Supplier for more information.

#### The ingredients of this product are reported in the following inventories:

**TSCA** All substances listed as active on the TSCA inventory  
**DSL** All components of this product are on the Canadian DSL  
**KECI** On the inventory, or in compliance with the inventory  
**IECSC** On the inventory, or in compliance with the inventory  
Please reach out to TEC Specialty Products LLC for further information regarding chemical inventories not listed above. **Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

## SECTION 16. OTHER INFORMATION

## SAFETY DATA SHEET


### TEC® POWER GROUT® 550-969 COFFEE

Version 1.0

Revision Date 04/21/2025

#### Further information

##### NFPA:



##### HMIS III:

|                        |           |
|------------------------|-----------|
| <b>HEALTH</b>          | <b>3*</b> |
| <b>FLAMMABILITY</b>    | <b>1</b>  |
| <b>PHYSICAL HAZARD</b> | <b>0</b>  |

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic