

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TEC® ISOLIGHT 359-WHITE  
Product code : 100000013606

##### Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac  
Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours) : 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

##### Recommended use of the chemical and restrictions on use

Recommended use : Cement, Adhesive

#### SECTION 2. HAZARDS IDENTIFICATION

##### Emergency Overview

|            |          |
|------------|----------|
| Appearance | powder   |
| Color      | white    |
| Odor       | odorless |

##### GHS Classification

Skin irritation : Category 2  
Serious eye damage : Category 1  
Skin sensitization : Category 1  
Carcinogenicity : Category 1A  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)  
Specific target organ toxicity - repeated exposure : Category 1

##### GHS label elements

Hazard pictograms :



Signal Word : Danger

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

#### Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.

#### Precautionary Statements:

**Prevention:** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

**Storage:** P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

#### Potential Health Effects

#### Carcinogenicity:

|      |                                        |            |
|------|----------------------------------------|------------|
| IARC | Group 1: Carcinogenic to humans        |            |
|      | quartz (SiO <sub>2</sub> )             | 14808-60-7 |
|      | cristobalite                           | 14464-46-1 |
|      | Quartz (SiO <sub>2</sub> )             | 14808-60-7 |
| OSHA | OSHA specifically regulated carcinogen |            |
|      | cristobalite                           | 14464-46-1 |
| NTP  | Known to be human carcinogen           |            |
|      | quartz (SiO <sub>2</sub> )             | 14808-60-7 |
|      | cristobalite                           | 14464-46-1 |
|      | Quartz (SiO <sub>2</sub> )             | 14808-60-7 |
|      | sulphur trioxide                       | 7446-11-9  |

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous ingredients

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

| Chemical name                      | CAS-No.    | Concentration [%] |
|------------------------------------|------------|-------------------|
| Cement, portland, chemicals        | 65997-15-1 | 30 - 50           |
| Limestone                          | 1317-65-3  | 10 - 20           |
| quartz (SiO <sub>2</sub> )         | 14808-60-7 | 10 - 20           |
| Ashes (residues)                   | 68131-74-8 | 10 - 20           |
| Calcium carbonate                  | 471-34-1   | 10 - 20           |
| Kieselguhr, soda ash flux-calcined | 68855-54-9 | 5 - 10            |
| gypsum                             | 13397-24-5 | 1 - 5             |
| cristobalite                       | 14464-46-1 | 1 - 5             |
| Calcium oxide                      | 1305-78-8  | 1 - 5             |
| calcium sulfate                    | 7778-18-9  | 1 - 5             |
| magnesium oxide                    | 1309-48-4  | 1 - 5             |
| calcium diformate                  | 544-17-2   | 1 - 5             |
| aluminium oxide                    | 1344-28-1  | 1 - 5             |
| Quartz (SiO <sub>2</sub> )         | 14808-60-7 | 0.1 - 1           |
| sulphur trioxide                   | 7446-11-9  | 0.1 - 1           |

Actual concentration is withheld as a trade secret

#### SECTION 4. FIRST AID MEASURES

|                                                             |                                                                                                                                                                                                                              |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice                                              | : In the case of accident or if you feel unwell, seek medical advice immediately.                                                                                                                                            |
| If inhaled                                                  | : If inhaled<br>Remove person to fresh air. If signs/symptoms continue, get medical attention.<br>Oxygen or artificial respiration if needed.                                                                                |
| In case of skin contact                                     | : Wash off with soap and water.<br>Remove contaminated clothing. If irritation develops, get medical attention.                                                                                                              |
| In case of eye contact                                      | : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.                                                                                                                   |
| If swallowed                                                | : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.<br>If conscious, drink plenty of water.<br>Never give anything by mouth to an unconscious person.         |
| Most important symptoms and effects, both acute and delayed | : Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye damage.<br>May cause respiratory irritation.<br>May cause cancer.<br>Causes damage to organs through prolonged or repeated exposure. |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

---

#### SECTION 5. FIRE-FIGHTING MEASURES

- |                                                |                                                                                                                                                                                                                 |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.                                                                                                                                      |
| Unsuitable extinguishing media                 | : None known.                                                                                                                                                                                                   |
| Specific hazards during fire fighting          | : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.<br>No hazardous combustion products are known |
| Hazardous combustion products                  | : No hazardous combustion products are known                                                                                                                                                                    |
| Specific extinguishing methods                 | :                                                                                                                                                                                                               |
| Further information                            | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                       |
| Special protective equipment for fire-fighters | : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.                                                                                             |

---

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |                                                                     |                                                                                                                                                                                                                                                                                          |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Refer to protective measures listed in sections 7 and 8.                                                                                                                                                                                                                               |
| Environmental precautions                                           | : Prevent product from entering drains.<br>Should not be released into the environment.                                                                                                                                                                                                  |
| Methods and materials for containment and cleaning up               | : Use approved industrial vacuum cleaner for removal.<br>Do not use compressed air for cleaning purposes.<br>Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. |

---

#### SECTION 7. HANDLING AND STORAGE

- |                         |                                                                                                                                                                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local/Total ventilation | : Use only with adequate ventilation.                                                                                                                                                                                                                                     |
| Advice on safe handling | : Avoid creating dust.<br>Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.<br>Take precautionary measures against static discharges.<br>Provide for appropriate exhaust ventilation and dust collection |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

at machinery.

Conditions for safe storage : Keep tightly closed in a dry and cool place.

Materials to avoid : No special restrictions on storage with other products.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

| Components                  | CAS-No.    | Value type<br>(Form of exposure)       | Control parameters / Permissible concentration | Basis     |
|-----------------------------|------------|----------------------------------------|------------------------------------------------|-----------|
| Cement, portland, chemicals | 65997-15-1 | TWA<br>(Respirable particulate matter) | 1 mg/m3                                        | ACGIH     |
|                             |            | TWA (total dust)                       | 15 mg/m3                                       | OSHA Z-1  |
|                             |            | TWA (respirable fraction)              | 5 mg/m3                                        | OSHA Z-1  |
|                             |            | TWA (Dust)                             | 50 Million particles per cubic foot            | OSHA Z-3  |
|                             |            | TWA (Total)                            | 10 mg/m3                                       | OSHA P0   |
|                             |            | TWA (Respirable fraction)              | 5 mg/m3                                        | OSHA P0   |
|                             |            | TWA (Total dust)                       | 10 mg/m3                                       | OSHA P0   |
|                             |            | TWA (respirable dust fraction)         | 5 mg/m3                                        | OSHA P0   |
|                             |            | PEL (Total dust)                       | 10 mg/m3                                       | CAL PEL   |
|                             |            | PEL (respirable dust fraction)         | 5 mg/m3                                        | CAL PEL   |
| Limestone                   | 1317-65-3  | TWA<br>(Respirable)                    | 5 mg/m3                                        | NIOSH REL |
|                             |            | TWA (total)                            | 10 mg/m3                                       | NIOSH REL |
|                             |            | TWA (Respirable)                       | 5 mg/m3                                        | NIOSH REL |
|                             |            | TWA (total)                            | 10 mg/m3                                       | NIOSH REL |
|                             |            | TWA (Respirable)                       | 5 mg/m3                                        | NIOSH REL |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

|                                    |            |                                     |                                  |           |
|------------------------------------|------------|-------------------------------------|----------------------------------|-----------|
|                                    |            | TWA (total)                         | 10 mg/m3                         | NIOSH REL |
|                                    |            | TWA (total dust)                    | 15 mg/m3                         | OSHA Z-1  |
|                                    |            | TWA (respirable fraction)           | 5 mg/m3                          | OSHA Z-1  |
|                                    |            | TWA (Total)                         | 15 mg/m3                         | OSHA P0   |
|                                    |            | TWA (Respirable fraction)           | 5 mg/m3                          | OSHA P0   |
|                                    |            | TWA (Total dust)                    | 15 mg/m3                         | OSHA P0   |
|                                    |            | TWA (respirable dust fraction)      | 5 mg/m3                          | OSHA P0   |
| quartz (SiO <sub>2</sub> )         | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m3                      | ACGIH     |
|                                    |            | TWA (total dust)                    | 30 mg/m3 / %SiO <sub>2</sub> +2  | OSHA Z-3  |
|                                    |            | TWA (respirable)                    | 10 mg/m3 / %SiO <sub>2</sub> +2  | OSHA Z-3  |
|                                    |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5 | OSHA Z-3  |
|                                    |            | TWA (Respirable dust)               | 0.05 mg/m3                       | NIOSH REL |
|                                    |            | TWA (Respirable fraction)           | 0.1 mg/m3                        | OSHA P0   |
|                                    |            | TWA (Respirable dust)               | 0.05 mg/m3                       | OSHA Z-1  |
|                                    |            | PEL (Respirable dust)               | 0.05 mg/m3                       | CAL PEL   |
|                                    |            | TWA (respirable dust fraction)      | 0.1 mg/m3                        | OSHA P0   |
| Calcium carbonate                  | 471-34-1   | PEL (Total dust)                    | 10 mg/m3                         | CAL PEL   |
|                                    |            | PEL (respirable dust fraction)      | 5 mg/m3                          | CAL PEL   |
|                                    |            | TWA (Respirable)                    | 5 mg/m3                          | NIOSH REL |
|                                    |            | TWA (total)                         | 10 mg/m3                         | NIOSH REL |
| Kieselguhr, soda ash flux-calcined | 68855-54-9 | TWA (Dust)                          | 20 Million particles per cubic   | OSHA Z-3  |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

|              |            |                                              |                                             |           |
|--------------|------------|----------------------------------------------|---------------------------------------------|-----------|
|              |            |                                              | foot                                        |           |
|              |            | TWA (Dust)                                   | 80 mg/m <sup>3</sup><br>/ %SiO <sub>2</sub> | OSHA Z-3  |
|              |            | TWA (Dust)                                   | 20 Million<br>particles per cubic<br>foot   | OSHA Z-3  |
|              |            | TWA (Dust)                                   | 80 mg/m <sup>3</sup><br>/ %SiO <sub>2</sub> | OSHA Z-3  |
|              |            | TWA                                          | 6 mg/m <sup>3</sup>                         | NIOSH REL |
|              |            | PEL                                          | 6 mg/m <sup>3</sup>                         | CAL PEL   |
| gypsum       | 13397-24-5 | TWA (total<br>dust)                          | 15 mg/m <sup>3</sup>                        | OSHA Z-1  |
|              |            | TWA<br>(respirable<br>fraction)              | 5 mg/m <sup>3</sup>                         | OSHA Z-1  |
|              |            | TWA (Total)                                  | 15 mg/m <sup>3</sup>                        | OSHA P0   |
|              |            | TWA<br>(Respirable<br>fraction)              | 5 mg/m <sup>3</sup>                         | OSHA P0   |
|              |            | TWA<br>(Inhalable<br>particulate<br>matter)  | 10 mg/m <sup>3</sup>                        | ACGIH     |
|              |            | TWA (Total<br>dust)                          | 15 mg/m <sup>3</sup>                        | OSHA P0   |
|              |            | TWA<br>(respirable<br>dust fraction)         | 5 mg/m <sup>3</sup>                         | OSHA P0   |
|              |            | PEL (Total<br>dust)                          | 10 mg/m <sup>3</sup>                        | CAL PEL   |
|              |            | PEL<br>(respirable<br>dust fraction)         | 5 mg/m <sup>3</sup>                         | CAL PEL   |
|              |            | TWA<br>(Inhalable<br>particulate<br>matter)  | 10 mg/m <sup>3</sup>                        | ACGIH     |
| cristobalite | 14464-46-1 | TWA<br>(Respirable<br>particulate<br>matter) | 0.025 mg/m <sup>3</sup>                     | ACGIH     |
|              |            | TWA<br>(Respirable<br>fraction)              | 0.05 mg/m <sup>3</sup>                      | OSHA P0   |
|              |            | TWA<br>(Respirable<br>dust)                  | 0.05 mg/m <sup>3</sup>                      | OSHA Z-1  |
|              |            | PEL<br>(Respirable<br>dust)                  | 0.05 mg/m <sup>3</sup>                      | CAL PEL   |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

|                 |           |                                    |            |           |
|-----------------|-----------|------------------------------------|------------|-----------|
|                 |           | TWA (respirable dust fraction)     | 0.05 mg/m3 | OSHA P0   |
|                 |           | PEL (respirable)                   | 0.05 mg/m3 | OSHA CARC |
| Calcium oxide   | 1305-78-8 | TWA                                | 2 mg/m3    | ACGIH     |
|                 |           | TWA                                | 5 mg/m3    | OSHA Z-1  |
|                 |           | TWA                                | 5 mg/m3    | OSHA P0   |
|                 |           | PEL                                | 2 mg/m3    | CAL PEL   |
| calcium sulfate | 7778-18-9 | TWA (Respirable)                   | 5 mg/m3    | NIOSH REL |
|                 |           | TWA (total)                        | 10 mg/m3   | NIOSH REL |
|                 |           | TWA (total dust)                   | 15 mg/m3   | OSHA Z-1  |
|                 |           | TWA (respirable fraction)          | 5 mg/m3    | OSHA Z-1  |
|                 |           | TWA (Total)                        | 15 mg/m3   | OSHA P0   |
|                 |           | TWA (Respirable fraction)          | 5 mg/m3    | OSHA P0   |
|                 |           | TWA (Inhalable particulate matter) | 10 mg/m3   | ACGIH     |
|                 |           | TWA (Total dust)                   | 15 mg/m3   | OSHA P0   |
|                 |           | TWA (respirable dust fraction)     | 5 mg/m3    | OSHA P0   |
|                 |           | PEL (Total dust)                   | 10 mg/m3   | CAL PEL   |
|                 |           | PEL (respirable dust fraction)     | 5 mg/m3    | CAL PEL   |
|                 |           | TWA (Inhalable particulate matter) | 10 mg/m3   | ACGIH     |
| magnesium oxide | 1309-48-4 | TWA (Inhalable particulate matter) | 10 mg/m3   | ACGIH     |
|                 |           | TWA (fume, total particulate)      | 15 mg/m3   | OSHA Z-1  |
|                 |           | TWA (Total particulate)            | 10 mg/m3   | OSHA P0   |
|                 |           | PEL (Fumes)                        | 10 mg/m3   | CAL PEL   |
|                 |           | TWA (Fume -                        | 10 mg/m3   | OSHA P0   |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

|                 |            |                                     |                     |          |
|-----------------|------------|-------------------------------------|---------------------|----------|
|                 |            | total particulate)                  |                     |          |
| aluminium oxide | 1344-28-1  | TWA (total dust)                    | 15 mg/m3            | OSHA Z-1 |
|                 |            | TWA (respirable fraction)           | 5 mg/m3             | OSHA Z-1 |
|                 |            | TWA (Total)                         | 10 mg/m3            | OSHA P0  |
|                 |            | TWA (Respirable fraction)           | 5 mg/m3             | OSHA P0  |
|                 |            | TWA (Respirable particulate matter) | 1 mg/m3             | ACGIH    |
|                 |            | TWA (Total dust)                    | 10 mg/m3            | OSHA P0  |
|                 |            | TWA (respirable dust fraction)      | 5 mg/m3             | OSHA P0  |
|                 |            | PEL (Total dust)                    | 10 mg/m3            | CAL PEL  |
|                 |            | PEL (respirable dust fraction)      | 5 mg/m3             | CAL PEL  |
|                 |            | TWA (Respirable particulate matter) | 1 mg/m3             | ACGIH    |
| Quartz (SiO2)   | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m3         | ACGIH    |
|                 |            | TWA (total dust)                    | 30 mg/m3 / %SiO2+2  | OSHA Z-3 |
|                 |            | TWA (respirable)                    | 10 mg/m3 / %SiO2+2  | OSHA Z-3 |
|                 |            | TWA (respirable)                    | 250 mppcf / %SiO2+5 | OSHA Z-3 |
|                 |            | TWA (Respirable fraction)           | 0.1 mg/m3           | OSHA P0  |
|                 |            | TWA (Respirable dust)               | 0.05 mg/m3          | OSHA Z-1 |
|                 |            | PEL (Respirable dust)               | 0.05 mg/m3          | CAL PEL  |
|                 |            | TWA (respirable)                    | 0.1 mg/m3           | OSHA P0  |

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

|  |  |                |  |  |
|--|--|----------------|--|--|
|  |  | dust fraction) |  |  |
|--|--|----------------|--|--|

**Engineering measures** : Use local exhaust ventilation or other engineering controls to minimize exposures.

#### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

**Filter type** : Particulates type

**Hand protection**  
**Material** : butyl-rubber

**Eye protection** : Safety glasses with side-shields

**Skin and body protection** : Long sleeved clothing  
Remove and wash contaminated clothing before re-use.  
Skin should be washed after contact.

**Protective measures** : Avoid contact with skin.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : powder  
**Color** : white  
**Odor** : odorless  
**Odor Threshold** : no data available  
: is not determined  
: is not determined  
**Flash point** : is not determined  
**Evaporation rate** : Not applicable  
**Upper explosion limit** : Upper flammability limit  
is not determined  
**Lower explosion limit** : Lower flammability limit  
is not determined  
**Density** : 7.5 lb/gal  
**Solubility(ies)**  
**Water solubility** : is not determined  
**Partition coefficient: n-** : Not applicable

**SAFETY DATA SHEET****TEC® ISOLIGHT 359-WHITE**

Version 1.0

Revision Date 03/14/2025

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : Not applicable

**SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Hazardous polymerization does not occur.

Hazardous decomposition products : No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method**Components:****Ashes (residues):**

Acute oral toxicity : LD50 Oral Rat: &gt; 2,000 mg/kg

**calcium diformate:**

Acute oral toxicity : LD50 Oral Rat: 2,650 mg/kg

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitization**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**SAFETY DATA SHEET****TEC® ISOLIGHT 359-WHITE**

Version 1.0

Revision Date 03/14/2025

**Reproductive toxicity**

No data available

**STOT-single exposure**

No data available

**STOT-repeated exposure**

No data available

**Aspiration toxicity**

No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Calcium oxide :**

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 1,070 mg/l  
Exposure time: 96 h  
Test Method: static test

**calcium sulfate :**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,970 mg/l  
Exposure time: 96 h  
Test Method: static test

**calcium diformate :**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): >= 1,000 mg/l  
Exposure time: 96 h  
Test Method: static test

**Persistence and degradability**

No data available

**Bioaccumulative potential****Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

#### Disposal methods

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.  
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

## SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SAFETY DATA SHEET

### TEC® ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### US State Regulations

##### California Prop 65

Please contact Supplier for more information.

#### The ingredients of this product are reported in the following inventories:

##### TSCA

All substances listed as active on the TSCA inventory

##### DSL


All components of this product are on the Canadian DSL

Please reach out to TEC Specialty Products, LLC for further information regarding chemical inventories not listed above. **Inventories Legend** TSCA (USA), DSL (Canada), REACH (Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

## SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



##### HMIS III:

|                        |           |
|------------------------|-----------|
| <b>HEALTH</b>          | <b>3*</b> |
| <b>FLAMMABILITY</b>    | <b>1</b>  |
| <b>PHYSICAL HAZARD</b> | <b>0</b>  |

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the TEC Specialty Products, LLC from its suppliers, and because the TEC Specialty Products, LLC has no control over the conditions of handling and use, the TEC Specialty Products, LLC makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the TEC Specialty Products, LLC assumes no responsibility for use or reliance thereon. It is the responsibility of the user of TEC Specialty Products, LLC to comply with all applicable federal, state and local laws and regulations.

## SAFETY DATA SHEET

### TEC<sup>®</sup> ISOLIGHT 359-WHITE

Version 1.0

Revision Date 03/14/2025

---