



Product Sustainability Quick Reference Guide

Our Focus on the Environment

TEC®, Parabond® and Fortane™ products are developed and manufactured with the environment in mind. Our goal is simple: Develop products that balance sustainability, usability, performance and value.

“**MAS Certified Green**” is a USGBC approved, third party lab that has certified each product as meeting “CDPH VOC Emissions”.

“**Floorscore**” is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring adhesives. It qualifies for many green building schemes including LEED v4.1, WELL, BREEAM, CHPS, and Green Globes.

“**CRI GLP**” is Carpet and Rug Institute’s Green Label Plus is a top-tier program for certification flooring adhesives, etc.

“**EPD**” is Environmental Product Declarations. A document which transparently communicates the environmental performance or impact of any product installed on jobsite over its lifetime.

“**HPD**” is Health Product Declaration®: Open Standard provides a rigorously-defined specification for a standard format and instructions to accurately, reliably and consistently report the material contents of a building product, and associated health information.

TEC® Surface Preparation	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
LiquiDam™ Penetrating Moisture Vapor Barrier (Part A, 213)	0	●				
LiquiDam™ Penetrating Moisture Vapor Barrier (Part B, 213)	0					
LiquiDam EZ™ Moisture Vapor Barrier (214)	1	●				
VersaPatch® Latex Modified Floor Patch (327)	0	●				
Fast-Set Deep Patch (305)	0	●				
PerfectFinish™ (320)	0	●				
Feather Edge Skim Coat (330)	0	●				
Floor Patch Pro (059)	0	●				
Ready To Use Skimcoat & Patch (896)	18					
Patch Additive (861)	12					
Multipurpose Primer (560)	0					
Level Set® Epoxy Primer (Part A, 052)	0					
Level Set® Epoxy Primer (Part B, 052)	0					
Level Set® LW-60 Ultra-Lightweight SLU (053)	0	●				
Level Set® Deep Pour 3 Self-Leveling Underlayment (DP3, 003)	0	●				
Level Set® 500 HF Self-Leveling Underlayment (500)	0	●				●
Level Set® 400 HF Self-Leveling Underlayment (400)	0	●				
Level Set® 300 Self-Leveling Underlayment (300)	0	●				
EZ Level® (323)	0	●				
Level Set® 200 Self-Leveling Underlayment (200)	0	●				●
Contractor Grade Self-Leveling Underlayment (567)	0	●				●
Fiber Reinforced Underlayment (565)	0					
HydraFlex™ Waterproofing Crack Isolation Membrane (316)	12	●				
Triple Flex™ Waterproofing Crack Isolation Membrane (Part A, 324)	0					
Triple Flex™ Waterproofing Crack Isolation Membrane (Part B, 324)	0					
Waterproofing and Crack Prevention Membrane	9.56					

Product Sustainability Quick Reference Guide

TEC Flooring and Wall Adhesives	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Flexera® High Tack Premium Universal Adhesive		●	●	●		●
Flexera® Premium Universal Adhesive (774)	1	●	●	●		
TotalFlex® XMS Tile Adhesive	40.1					
The Perfect Putdown® Premium Carpet and Flooring Adhesive (717)	0	●	●	●		
Stair Tread Adhesive (470)	<10	●	●	●		
Contract Multipurpose Adhesive (700)	0	●	●	●		
Premium Fast Grab Carpet Adhesive (704)	0	●	●	●		
Double-Stick Carpet Adhesive (902)	0	●	●	●		
Releasable Pressure Sensitive Adhesive (749)	0	●	●	●		
Indoor/Outdoor Carpet Adhesive (975)	0	●	●	●		
Carpet Pad Adhesive (10)	0	●	●			
Universal Solvent-Free Seam Sealer (131)	34	●	●			
Clear Thin Spread Adhesive (713)	0	●	●	●		
Premium Cove Base Adhesive (714)	10	●	●	●		
Premium Cove Base Adhesive (White, 714W)	5	●	●	●		
Wood Secure™ Premium Wood Adhesive	<8					
Wood Assure™ Premium Urethane Wood Flooring Adhesive and Moisture Barrier (804)	n/a	●	●			
Wood Endure™ Advanced Performance Wood Flooring Adhesive (806)	n/a					
Wood Go™ Urethane Wood Flooring Adhesive (802)	97					
Wood Ready™ Engineered Wood Flooring Adhesive (800)	8	●	●	●		
TEC Mortars	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Crack Isolation Polymer Modified Mortars						
Isolight™ 1/8" Crack Isolation Mortar (Gray, 358; White, 359)	0	●			●	
Fast Set Polymer Modified Mortars						
Fast Set 3N1™ Performance Mortar (Gray, 517; White, 518)	0	●			●	
Fast Set Ultimate Large Tile Mortar (Gray, 386; White, 387)	0	●			●	
Quik Flex® Accelerated Thin Set Mortar (Gray, 395; White, 396)	0	●			●	
Fast Set Mortar (395)	0				●	
Polymer Modified Mortars						
TotalFlex® 150 Universal Mortar	0	●			●	
TotalFlex® 110 Universal Mortar	0	●			●	
3N1™ Performance Mortar (Gray, 384; White, 385)	0	●			●	
Ultimate Large Tile Mortar (Gray, 382; White, 383)	0	●			●	●
Ultimate 6 Plus Mortar (White, 487)	0	●			●	
Super Flex™ Ultra-Premium Polymer Modified Mortar (Gray, 392; White, 393)	0	●			●	
Full Flex® Premium Thin Set Mortar (Gray, 390; White, 391)	0	●			●	●
Sturdi Flex™ Thin Set Mortar (Gray, 345; White, 346)	0	●			●	
SturdiLight™ Lightweight Latex Modified Thin Set Mortar (Gray, 354; White, 355)	0	●			●	
PermaFlex® 300 LHT Large Heavy Tile Mortar (Gray, 044; White, 045)	0	●			●	●
PermaFlex® 300 (Gray, 034; White, 035)	0	●			●	
Full Contact Mortar (369)	0	●			●	
Glass Block Mortar (363)	0	●			●	
PermaLastic® 200 Polymer Modified Thin Set Mortar (Gray, 426; White 427)	0	●			●	
PermaLastic® 100 Polymer Modified Thin Set Mortar (Gray, 424; White 425)	0	●			●	
PermaLastic® LHT Polymer Modified Mortar (Gray, 434; White 435)	0	●			●	
Ultimate Premixed Mortar (130)	27				●	

Product Sustainability Quick Reference Guide

TEC Mortars <i>continued</i>	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Dry Set Mortars						
Uncoupling Membrane Mortar (Gray, 337; White 338)	0	●			●	
Full Set Plus® Unmodified Thin Set Mortar (Gray, 380; White, 381)	0	●			●	
Full Set Plus® Unmodified Thin Set Mortar, Summer (Gray, 380)	0	●			●	
PermaSet® 200 (Gray, 030; White, 031)	0	●			●	
Mortar Additives						
XtraFlex™ Acrylic Latex Additive (872)	12					
Acrylbond® AMA Acrylic Latex Additive (862)	8					
TEC Mastics	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Double Duty™ Plus White Ceramic Tile Adhesive (123)	44					
Double Duty™ Ceramic Tile Adhesive (122)	137					
Type 1 Mastic (101)	1.3					
TEC Grout** and Grout Additives	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Premixed Vinyl Tile Grout (639)	15				●	
Design FX® Design Inspired Stain Proof Grout (546)	10				●	
InColor™ Advanced Performance Grout (575)	10				●	
Ready To Use Grout (647)	28.1				●	
Power Grout® Ultimate Performance Grout (550)	0	●			●	●
AccuColor® Plus Grout (450)	0	●			●	●
AccuColor EFX® Epoxy Mortar and Grout (Part A, 440)	0					
AccuColor EFX® Epoxy Mortar and Grout (Part B, 440)	0					
AccuColor EFX® Epoxy Mortar and Grout (Part C, 440)	0					
AccuColor EFX® Clean-up Water Concentrate (442)	0					
AccuColor® Premium Grout, Sanded (650)	0	●			●	
Sanded Adhesive & Grout (691)	29				●	
AccuColor® Premium Grout, Unsanded (620)	0	●			●	●
Unsanded Adhesive & Grout (631)	35				●	
Acrylic Grout Additive (869)	2				●	
Grout Colorant (505)	59					
TEC Caulks and Sealants	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
AccuColor 100® 100% Silicone Sealant (155)	40					
AccuColor® Siliconized Acrylic Caulk, Sanded (850)	12					
AccuColor® Siliconized Acrylic Caulk, Unsanded (820)	14					
Joint/Crack Filler	0					
Parabond® Adhesives	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Signature Series DS-902 Dubl-Stik Adhesive	<1	●	●	●		
Signature Series 4092 Economy Grade Flooring Adhesive	n/a	●	●	●		
Signature Series 4094 Premium Multi Purpose Adhesive	<1	●	●	●		
Signature Series 4096 Fast Grab Multi Purpose Adhesive	0.77	●	●	●		
Signature Series 4099 High Performance Multi Purpose Adhesive	<1	●	●	●		
Fusion Series 5082 Vinyl Tile & Plank Adhesive	<1	●	●	●		

Product Sustainability Quick Reference Guide

Parabond Adhesives <i>continued</i>	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Signature Series 5060 Pressure Sensitive Adhesive	<1	●	●	●		
Signature Series 5080 Pressure Sensitive Adhesive	6	●	●	●		
Fusion Series 4500 Clear Thin Spread VCT	<1	●	●	●		
Fusion Series 4700 Rubber Tile and Stair Tread Adhesive	<10	●	●	●		
Parabond M-4263 Solvent-Free Universal Carpet Seam Sealer	<21	●	●	●		
Fusion X Wall Base Adhesive	<1	●	●	●		
Fusion Series 5092 Universal Pressure Sensitive Adhesive	<1	●	●	●		
Fusion Series 5092 HT Universal Pressure Sensitive Adhesive	<1	●	●	●		
AIM™ 382 Solvent-Free Pedestal Adhesive	0	●	●	●		
Millennium Series 2009 Premium Wood Flooring Adhesive	<8	●	●	●		
M-2850 Outdoor & Indoor Carpet Adhesive	<1	●	●	●		
Fortane™ Adhesives	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI GLP	EPD Industry-wide Type III	HPD (any are available upon request)
Fortane™ LD Polyurethane Wood Floor Adhesive	<100		●			
Fortane™ One Polyurethane Moisture Vapor Barrier & Wood Flooring Adhesive	0		●			
Fortane™ Zero Modified Silyl Wood Flooring Adhesive	0		●			
Fortane™ Universal PSA	<1		●			
Fortane™ MBA Polyurethane Moisture Barrier Adhesive	<100		●			

Reference Guide for Applicable Credits		
Low-Emitting Materials	Points	Requirement
IEQ Credit 4.2	1	All paints and coatings (including floor coatings, primers and sealers) must not exceed the VOC content limits established in South Coast Air Quality Management District (SCAQMD) Rule #1113. SCAQMD #1168 sets volatile organic compound limits for paints and coatings applied on site.

The trademarks listed on this certification sheet, unless otherwise noted, are owned by TEC Specialty Products LLC.

The information provided herein has been prepared in good faith on the basis of information available at the time of publication. Because of variations that take place during production in normal working and environmental conditions, TEC Specialty Products LLC cannot be responsible for the consequence of variations in such conditions or for unforeseen conditions.