

SAFETY DATA SHEET

TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TEC® VINYL TILE GROUT LIGHT SMOKE
Product code : 100000013556

Manufacturer or supplier's details

Company : TEC Specialty Products
Address : 1105 South Frontenac
Aurora, IL, 60504
Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours) : 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Grout

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Color	brown
Odor	sweet

GHS Classification

Germ cell mutagenicity : Category 1B
Carcinogenicity : Category 1B

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements:

H340 May cause genetic defects. H350 May cause cancer.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves, protective clothing, eye protection and face protection.

SAFETY DATA SHEET**TEC® VINYL TILE GROUT LIGHT SMOKE**

Version 1.0

Revision Date 11/12/2025

Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention.**Storage:** P405 Store locked up.**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.**Potential Health Effects****Carcinogenicity:****IARC**

Group 1: Carcinogenic to humans

Quartz (SiO₂)

14808-60-7

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogen

Quartz (SiO₂)

14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Quartz (SiO ₂)	14808-60-7	30 - 60
Limestone	1317-65-3	10 - 30
stoddard solvent	8052-41-3	0.1 - 1

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
- In case of skin contact : Wash off with soap and water.
Get medical attention if irritation develops and persists.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
- Most important symptoms and effects, both acute and delayed : May cause genetic defects.
May cause cancer.

SAFETY DATA SHEET

TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|--|---|
| Suitable extinguishing media | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
| Unsuitable extinguishing media | : None known. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Specific extinguishing methods | : |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Special protective equipment for fire-fighters | : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Refer to protective measures listed in sections 7 and 8. |
| Environmental precautions | : Prevent product from entering drains.
Should not be released into the environment. |
| Methods and materials for containment and cleaning up | : Ventilate the area.
Scrape up.
Shovel into suitable container for disposal. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|---|
| Local/Total ventilation | : Use only with adequate ventilation. |
| Advice on safe handling | : Use only with adequate ventilation/personal protection.
Keep container closed when not in use. |
| Conditions for safe storage | : Keep container tightly closed in a dry and well-ventilated place.
Store in original container. |
| Materials to avoid | : Do not store together with oxidizing and self-igniting products.
Do not freeze. |

SAFETY DATA SHEET

TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m ³	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
Limestone	1317-65-3	TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total)	15 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
		TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	500 ppm	OSHA Z-1

SAFETY DATA SHEET

TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

			2,900 mg/m3	
		TWA	100 ppm 525 mg/m3	OSHA P0
		PEL	100 ppm 525 mg/m3	CAL PEL

Personal protective equipment

- Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Use NIOSH approved respiratory protection.
- Filter type : Dust/mist/aerosol
- Hand protection
Material : Nitrile rubber
- Eye protection : Safety glasses with side-shields
- Skin and body protection : Skin should be washed after contact.
- Protective measures : Avoid contact with skin.
- Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Color : brown
- Odor : sweet
- Odor Threshold : no data available
- pH : is not determined
8.5 - 9.5
- : is not determined
- : is not determined
- Evaporation rate : is not determined
- Upper explosion limit : Upper flammability limit
is not determined
- Lower explosion limit : Lower flammability limit
is not determined
- Vapor pressure : is not determined
- Density : 12.0 - 13.8 lb/gal
- Solubility(ies)
- Water solubility : is not determined

SAFETY DATA SHEET

TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

Partition coefficient: n-octanol/water : no data available

Autoignition temperature : is not determined

Viscosity
Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

SAFETY DATA SHEET

TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container. Do not dispose of waste into sewer.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET**TEC® VINYL TILE GROUT LIGHT SMOKE**

Version 1.0

Revision Date 11/12/2025

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**SARA 311/312 Hazards** : Germ cell mutagenicity
Carcinogenicity**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ethylene glycol

107-21-1

US State Regulations**California Prop 65**

Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:**TSCA**

All substances listed as active on the TSCA inventory

DSL

All components of this product are on the Canadian DSL

Please reach out to TEC Specialty Products LLC for further information regarding chemical inventories not listed above. **Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)**SECTION 16. OTHER INFORMATION**

SAFETY DATA SHEET


TEC® VINYL TILE GROUT LIGHT SMOKE

Version 1.0

Revision Date 11/12/2025

Further information

NFPA:



HMIS III:

HEALTH	0*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic