

TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TEC® 639 VINYL TILE GROUT- PEARL

Product code : 100000014900

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours): 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Grout

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Color	off-white
Odor	sweet

GHS Classification

Germ cell mutagenicity : Category 1B Carcinogenicity : Category 1B

GHS label elements

Hazard pictograms

Signal Word : Danger

Hazard Statements:

H340 May cause genetic defects. H350 May cause cancer.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves, protective clothing, eye protection and face protection.



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

> Quartz (SiO2) 14808-60-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

> Quartz (SiO2) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Quartz (SiO2)	14808-60-7	30 - 60
Limestone	1317-65-3	10 - 30
stoddard solvent	8052-41-3	0.1 - 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

If inhaled Remove person to fresh air. If signs/symptoms continue, get

medical attention.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do not induce vomiting. Seek medical attention if symptoms

develop. Provide medical care provider with this SDS.

Most important symptoms

and effects, both acute and

delayed

: May cause genetic defects.

May cause cancer.



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: None known.

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

methods

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

: Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

: Refer to protective measures listed in sections 7 and 8.

emergency procedures

Environmental precautions : Prevent product from entering drains.

Should not be released into the environment.

Methods and materials for

: Ventilate the area.

containment and cleaning up Scrape up.

Shovel into suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Use only with adequate ventilation/personal protection.

Keep container closed when not in use.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in original container.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

Do not freeze.



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
Limestone	1317-65-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total)	15 mg/m3	OSHA P0
		TWA (Respirable fraction)	5 mg/m3	OSHA P0
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	500 ppm	OSHA Z-1



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

	2,900 mg/m3	
TWA	100 ppm 525 mg/m3	OSHA P0
PEL	100 ppm 525 mg/m3	CAL PEL

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Use NIOSH approved respiratory protection.

Filter type : Dust/mist/aerosol

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Skin and body protection : Skin should be washed after contact.

Protective measures : Avoid contact with skin.

Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid
Color : off-white
Odor : sweet

Odor Threshold : no data available pH : is not determined

8.5 - 9.5

is not determinedis not determined

Evaporation rate : is not determined Upper explosion limit : Upper flammability

: Upper flammability limit is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined

Density : 12.0 - 13.8 lb/gal

Solubility(ies)

Water solubility : is not determined



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

Partition coefficient: n-

octanol/water

: no data available

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0

Revision Date 11/13/2025

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container. Do not dispose of waste into sewer.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0 Revision Date 11/13/2025

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Germ cell mutagenicity

Carcinogenicity

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ethylene glycol 107-21-1

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA

All substances listed as active on the TSCA inventory

All components of this product are on the Canadian DSL

Please reach out to TEC Specialty Products LLC for further information regarding chemical inventories not listed above. Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AllC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines),

IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION




TEC® 639 VINYL TILE GROUT- PEARL

Version 1.0

Revision Date 11/13/2025

Further information





Special hazard

HMIS III:

HEALTH	0*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic